




Sources of Christo Radev's professional experience



CPU, MCU, SoC, OS and programming languages used to gain professional experience in the time



CPU, MCU, SoC and system performance used to gain professional experience (CPU frequency vs. RAM size)



Devices, MCUs and SoCs used to gain professional experience in embedded systems



Date	Device	SoC/MCU	Core	MHz	RAM [MB]	FLASH [MB]	100MB Eth	1GB Eth	Wireless	HD	USB 2.0	USB 3.0	Other
1.12.2010	Cinterion TC65 Terminal	TC65 Module (Java IMP-NG profile)							GSM 850/900/1800/1900				SIM, 1xRS232, 2xADC, SPI, I2C, GPIO, Audio Out, Antenna
9.1.2009	Grandstream HandyTone 488	ATA & VoIP					1+1						1xFXS, 1xFXO / PSTN Pass-through
8.10.2015	Linksys WRT1900ACS	Marvell Armada 385 88F6820	2 x ARM v7	1 600	512	128		1+4	802.11a/b/g/n/ac	eSATA	1	1	
1.1.2013	D-Link DIR-860L	Broadcom BCM47081A0	2 x Cortex-A9	880	128	128		1+4	802.11a/b/g/n/ac			1	1xUART
1.12.2005	Linksys WRV54G	Intel IXP425	Intel XScale	266	32	8	1+4		802.11b/g				1xUART, miniPCI, JTAG
1.12.2005	Linksys WRT54GS v.1.0	Broadcom BCM4712	MIPS32	200	32	8	1+4		802.11b/g				1xUART, JTAG
1.3.2005	Netgear WGT634U	Broadcom BCM5365	MIPS32	200	32	8	1+4		802.11b/g		1		1xUART
1.1.2005	Linksys NSLU2	Intel IXP420	Intel XScale	133	32	8	1				2		2xUART, JTAG
1.12.2004	Linksys WRT54G v.1.0	Broadcom BCM4702	MIPS32	125	16	4	1+4		802.11b/g				1xUART, JTAG
1.4.2015	Olimex A20-OLinuXino-LIME2-e8G	Allwinner A20	2 x Cortex-A7	1 000	1GB	8GB		1		SATA 2	2+1-otg		eMMC, uSD, HDMI, Audio I/O, 2xUEXT, GPIO
1.9.2014	Olimex A20-OLinuXino-LIME2	Allwinner A20	2 x Cortex-A7	1 000	1GB	8GB		1		SATA 2	2+1-otg		uSD, HDMI, Audio I/O, 2xUEXT, GPIO
1.4.2014	Olimex A20-SOM-4GB	Allwinner A20	2 x Cortex-A7	1 000	1GB	4GB		1		SATA 2	2+1-otg		uSD, HDMI, LCD, Audio I/O, GPIO
1.4.2014	Olimex A20-SOM-EVB	Allwinner A20	2 x Cortex-A7	1 000	1GB	4GB		1		SATA 2	2+1-otg		uSD, Camera, HDMI, VGA, Audio I/O, 2xUEXT, GPIO
1.1.2014	Olimex A13-OLinuXino-WiFi	Allwinner A13	Cortex-A8	1 000	512	8GB			802.11b/g		3+1-otg		uSD, VGA, Audio I/O, 2xUEXT, GPIO
1.1.2014	Olimex A13-SOM-512 + A13-SOM-WIFI-4	Allwinner A13	Cortex-A8	1 000	512	4GB			802.11b/g		1-otg		uSD, UART, GPIO
1.9.2013	Olimex A10-OLinuXino-LIME	Allwinner A10	Cortex-A8	1 000	512	8GB	1			SATA 2	2+1-otg		uSD, HDMI, LCD, GPIO
1.1.2009	TI BeagleBoard	TI OMAP3530	Cortex-A8	720	256	256					1+1-otg		DVI-D, S-Video, Audio I/O, SD/MMC/SDIO, RS232, GPIO, JTAG
2.4.2007	Gunstix Verdex XL6P	Marvell PXA270	Intel Xscale	600	128	32	1				2		LCD, uSD, 3xUART, AC97, SPI, I2C, GPIO, JTAG
1.9.2013	Olimex iMX233-OLinuXino-Maxi	iMX233	ARM926j	454	64			1			2		uSD, TV Video Out, Audio I/O, UEXT, GPIO
1.10.2014	Olimex RT5350F-OLinuXino	Ralink RT5350 F	MIPS24KEc	360	32	8	5		802.11n		1		5-port ethernet switch, 2xUART, SPI, I2C, I2S, GPIO, JTAG, Antenna
1.10.2014	RT5350F-OLinuXino-EVB rev. A	Olimex RT5350F-OLinuXino	MIPS24KEc	360	32	8	2		802.11n		1		5-port ethernet switch, UART, 2xRelay, UEXT, GPIO
1.9.2009	Glomation GESBC-9302E	CS EP9302	ARM920T	200	64	16	1				2		2xUART, RS232, ADC, DAC, SPI, GPIO, JTAG
24.2.2006	Cirrus Logic EDB9315A	Cirrus Logic EP9315	ARM920T	200	64	16	1			IDE	2		LCD, Audio In/Out, VGA, 3xUART, GPIO, JTAG
1.1.2009	Olimex SAM9-L9260	Atmel AT91SAM9260	ARM926EJ-S	180	64	512	1				1+1-dev		SD/MMC, RS232, UEXT, GPIO, JTAG
17.4.2007	AVR32 NGW100	Atmel 32AP7000	AVR-32	140	32	8	2				1-dev		SD/MMC, RS232, ATTiny24, GPIO, JTAG
1.1.2014	Olimex A13-LCD7"-TS												7" LCD, TS, Cable
1.4.2016	Olimex MOD-WIFI-ESP8266-DEV	EPS8266EX	L106	80	160KB	2	2		802.11 b/g/n		1		SPI, I2C, I2S, ADC, GPIO
1.4.2016	Olimex MOD-WIFI-ESP8266-DEV	MOD-WIFI-ESP8266-DEV	L106	80	160KB	2	2		802.11 b/g/n		1		UART, SPI, I2C, I2S, ADC, GPIO, UEXT, Relay
1.4.2011	STM32W RF Control Kit	STMicroelectronics STM32WL	Cortex M4+M0	48	64KB	256KB			802.15.4				3xUART, 2xSPI, 3xI2C, ADC, DAC, GPIO
1.4.2011	Atmel AVR Raven Kit	ATmega3290P + ATmega1284P + AT86RF231	1+1 AVR-8	20	2/16KB	32/128KB			802.15.4		1		LCD, GPIO
1.4.2011	Atmel ATmega128RFA1-EK1	Atmel ATmega128RFA1	AVR-8	16	16KB	128KB			802.15.4				2xUART, 10-bit ADC, SPI, TWI, GPIO, JTAG, Antenna
1.10.2016	Olimex STM32-E407	STMicroelectronics STM32F407ZGT6	Cortex M4	168	196KB	1	1				1+1-otg		uSD, 6xUART, 3xSPI, 3xI2C, 2xCAN, 3xADC, 2xDAC, UEXT, GPIO, JTAG
1.10.2016	Olimex STM32-H405	STMicroelectronics STM32F405RG	Cortex M4	168	196KB	1					1+1-otg		6xUART, 3xSPI, 3xI2C, 2xCAN, 3xADC, 2xDAC, SDIO, GPIO, JTAG
1.8.2013	NXP mbed	NXP LPC1768	Cortex M3	100	64KB	512KB	1				1-otg		4xUART, CAN 2.0, 3xSPI/SSP, 3xI2C, I2S, ADC, DAC, GPIO, JTAG
1.8.2010	Olimex STM32-LCD	STMicroelectronics STM32F103ZE	Cortex M3	72	64KB	512KB					1-otg		LCD, uSD/MMC, 3xUENT, JTAG
1.8.2010	Olimex STM32-P103	STMicroelectronics STM32F103RBT6	Cortex M3	72	20KB	128KB					1+1-dev		CAN, 2xI2C, 2xADC 12 bit, 3xUART, 2xSPI, GPIO, UEXT, JTAG
19.1.2009	STMicroelectronics STM3210E-EVAL/A	STMicroelectronics STM32F103ZET6	Cortex M3	72	1	16					1		LCD, uSD, 2xRS232, CAN 2.0, I2S, GPIO, JTAG
1.4.2009	Olimex ATMega128 HB	Atmel ATmega128-16AU	AVR-8	16	4KB	128KB							2xUART, SPI, I2C, TWI, ADC, GPIO, JTAG
1.4.2009	Olimex MSP430-P1232M	TI MSP430F1232	MSP430	16	4KB	92KB							2xUART, 2xSPI, 2xI2C, ADC, GPIO, JTAG
1.9.2017	STMicroelectronics STM32F429I-DISCO	STMicroelectronics STM32F429ZIT6	Cortex M4	180	260KB + 8	2	1				1+1-otg		LCD, MEMS, 8xU(S)ART, 6xSPI, 5xI2C, 3xADC, 2xDAC, GPIO, ST-LINK
1.4.2018	STMicroelectronics Nucleo-64 STM32L433	STMicroelectronics STM32L433RCT6PU	ULP Cortex M	80	64KB	256KB					1		4xUSART, 3xI2C, I2S, 3xSPI, CAN, ADC, 2xDAC, GPIO, ST-Link, Arduino
1.9.2017	STMicroelectronics STM32F3-Discovery	STMicroelectronics STM32F303VCT6	Cortex M4	72	48KB	256KB					1		MEMS, 5xU(S)ART, 3xSPI, 2xI2C, 4xADC, 2xDAC, GPIO, ST-LINK
1.1.2010	Olimex Olimexino-STM32	STMicroelectronics STM32F103RBT6	Cortex M3	72	20KB	128KB					1+1-dev		CAN, 2xI2C, 2xADC 12 bit, 3xUART, 2xSPI, GPIO, UEXT, JTAG
1.8.2018	STMicroelectronics Nucleo-64 STM32F072	STMicroelectronics STM32F072RBT6	Cortex M0	48	16KB	128KB					1		4xUSART, 2xI2C, 2xSPI, CAN, ADC, GPIO, On-board ST-Link, Arduino
1.8.2014	STMicroelectronics STM32 Value Discovery	STMicroelectronics STM32F100RBT6B	Cortex M3	24	8KB	128KB							3xUART, 2xI2C, 2xSPI, ADC, GPIO, On-board ST-Link
1.4.2018	Olimex AVR-T32U4 (Leonardo)	Atmel ATMEGA32U4	AVR-8	16	2,56KB	32KB					1-dev		UART, SPI, I2C, TWI, ADC, GPIO
1.4.2018	Olimex Olimexino-32U4	Atmel ATMEGA32U4	AVR-8	16	2,56KB	32KB					1-dev		UART, SPI, I2C, TWI, ADC, GPIO, Arduino layout
1.4.2018	Olimex Olimexino-nano + -bat	Atmel ATMEGA32U4	AVR-8	16	2,56KB	32KB					1-dev		UART, SPI, I2C, TWI, ADC, GPIO, Battery
20.12.2017	Decaway DWM1000 module								802.15.4-2011				UWB 2-way ranging and TDOA, SPI, GPIO, Internal chip antenna

TIOBE index of popularity and programming languages used to gain professional experience


Ranked by TIOBE index of the popularity		TIOBE Index for Dec '20/'19			Long Term History (recorded by TIOBE)										Programming languages used																
Programming Language	The Winner of the Year	Dec '20	Monthly Change	Dec '19	2020	2015	2010	2005	2000	1995	1990	1985	Used in various projects (Year, CPU, OS, SW, Usage)																		
		▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼	▼							
C	'19, '17, '08	1	▲	2	1	2	2	1	1	1	1	1	'83-'20, MC6800/MOS 6502/MC680x0/x86-64/x51/AVR-8/SAM9260/EP9302/AVR-32/E1-32/ARM Cortex M3/M4/A7/A8, FW/MDOS/MS-DOS/Windows/OS-9/Unix/QNX/Linux/eCOS/uSmartOS/FreeRTOS/ChibiOS																		
Java	'15, '05	2	▼	1	2	1	1	2	3	29	-	-	'03-'20, x86-64/MIPS32/Xscale/TC65/E1-32/ARM Cortex A7/A8, FW/Windows/Mac-OS/Linux, OSGI/Eclipse/Web staff																		
Python	'20, '18, '10, '07	3	-	3	3	5	6	7	22	13	-	-	'03-'20, x86-64/MIPS32/Xscale/ARM Cortex A7/A8, Windows/Linux, Web staff																		
C++	'03	4	-	4	4	3	3	3	2	2	2	8	'00-'01, R4000/ERS-210, Aperios, FW for AIBO robots/RoboCup 2001; '00-'20, x86-64, Windows/Linux, C++ Builder/Eclipse; '10-'20, Atmel AVR 8bit/AtMega32U4/ARM Cortex M3/M4, FW, Arduino																		
C#	-	5	-	5	5	4	5	6	10	-	-	-	'03-'08, x86, Windows, Web staff; '10-'11, Teklogix 7530, Windows CE																		
Visual Basic	-	6	-	6	-	-	-	-	-	-	-	-	'00-'20, x86-64, Windows, MS Office, Scientific Calculations																		
JavaScript	'14	7	-	7	6	8	10	10	7	-	-	-	'15-'20, x86-64/ARM Cortex A7/A8, Windows/Mac-OS/Linux, NodeJS/Web staff																		
PHP	'04	8	-	8	7	6	4	4	19	-	-	-	'07-'20, x86/MIPS32/Xscale/ARM Cortex A7/A8, Windows/Linux, Web staff																		
R	-	9	▲	16	9	14	46	-	-	-	-	-	-	-																	
SQL	-	10	-	9	8	-	-	-	-	-	-	-	'95-'03, x86, Windows/NT, Sybase SQL/Delphi/C++ Builder; '07-'20, x86/MIPS32/Xscale/ARM Cortex A7/A8, MySQL/Windows/Linux, .NET/PHP/Web staff																		
Groovy	-	11	▲	22	-	-	-	-	-	-	-	-	-	-	-																
Assembly language	-	12	▲	14	-	-	-	-	-	-	-	-	'79-'89, MC6800/MOS 6502, FW/MDOS; '84-'89, LSI 1123, RT-11; '88-'89, MC680x0, OS-9/Unix; '95-'96, x86, MS-DOS; '03-'08, E1-32, HyNetOS/Linux																		
Swift	-	13	▼	10	10	15	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Perl	-	14	▲	20	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Ruby	'06	15	▼	11	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Go	'16, '09	16	▼	15	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
MATLAB	-	17	-	17	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Delphi/Object Pascal	-	18	▼	12	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	'94-'03, x86, Windows, Delphi, Desktop Applications			
Objective-C	'12, '11	19	▼	13	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
PL/SQL	-	20	▲	24	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Transact-SQL	'13	25	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Lisp	-	27	-	-	29	26	14	13	9	6	4	2	'86-'89, MC680x0, OS-9/Unix; '87-'93, x86, MS-DOS/Windows, Acad																		
Fortran	-	32	-	-	31	21	24	14	13	14	3	5	'78-'79, IBM System 360, Punched card OS, Scientific Calculations																		
Ada	-	34	-	-	34	23	21	16	17	3	9	3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Lua	-	43	-	-	-	-	-	-	-	-	-	-	'14-'18, x86-64, Windows, FEMM, Scientific Calculations																		
Basic	-	-	-	-	-	-	-	-	-	-	-	-	'83-'89, Apple II, ROM/FDD, Scientific Calculations																		
Occam	-	-	-	-	-	-	-	-	-	-	-	-	'89-'93, T414/T800, -/Helios, Own HW/SW Development System																		
Parallel C	-	-	-	-	-	-	-	-	-	-	-	-	'89-'93, T414/T800, -/Helios, Own HW/SW Development System																		
Parallel Fortran	-	-	-	-	-	-	-	-	-	-	-	-	'89-'93, T414/T800, -, Scientific Calculations																		
Focal	-	-	-	-	-	-	-	-	-	-	-	-	'78-'79, CM-4, Punched tape OS, Scientific Calculations																		

Because of the long professional life and great number of use cases used programming languages are compared to the index of popularity calculated by TIOBE. As can be seen from the table, nine of the ten most popular programming languages were used back in time. Another ten used programming languages fall among the top fifty of TIOBE's lists for the year 2020. On the other hand almost all 20 programming languages used in time fall among the top fifty of TIOBE's lists for the last 35 years.







Own project: Adroid the Open S.T.E.A.M. robot platform (2024)



Own project: Multichannel Energy Metering (MEM) system and its test bench (2023)



Own project: Unified Multicore Low Power IoT Platform (2023)




	Arduino board / MCU			Uno / ATMega328			Leonardo / ATMega32U4			D1 R32 / ESP32			Pi Pico / RP2040			Pi Pico / RP2040 (Overclocked)			Unified App			AVR128fs48		ESP32-S3		
	Adafruit	TFT	Speed up	Adafruit	TFT	Speed up	Adafruit	TFT_eSPI (3MHz)	Speed up	Adafruit	TFT_eSPI (27MHz)	Speed up	Adafruit	TFT_eSPI (82.5MHz)	Speed up	Adafruit	TFT_eSPI (27MHz)	Speed up	Adafruit	Address	Address	Address	Address			
Memory usage [B]																										
Stack	23,736	23,870	32.5%	28,874	23,992	23,760	29,261	29,261	32,772	32,786	32,786	32,786	32,786	32,786	32,786	32,786	32,786	32,786	32,786	32,786	32,786	32,786	32,786	32,786		
Flash used	(73.5%)	(67.80%)		(90.24%)	(83.68%)		(88.13%)	(23.50%)		(20.91%)	(20.91%)		(15.67%)	(17.78%)		(20%)	(23%)		(46%)	(38.65%)		(22.52%)				
SRAM used	590	796	1.3%	915	711	37,264	71,386	71,386	71,386	71,766	71,766	71,766	71,766	71,766	71,766	71,766	71,766	71,766	71,766	71,766	71,766	71,766	71,766	71,766		
Benchmarks [ms]																										
Screen fill	1,496,456	870,220	1.72x	1,50,598	874,600	1.72x	2,120,995	274,575	9.09x	904,666	281,577	2.14x	497,481	107,972	4.66x	97,267	1,603,604	295,261	295,261	1,604,480	134,560	1,314,720	1,314,720			
Text	147,088	60,486	2.43x	147,820	60,724	2.43x	99,600	32,899	6.49x	48,482	18,831	2.41x	30,599	8,088	3.78x	8,070	114,885	32,499	32,499	101,897	4,464	30,254	23,741	43,648	546,199	339,491
Lines	1,171,116	242,732	4.89x	1,178,004	243,988	4.89x	986,746	33,491	30.97x	454,686	101,897	4.46x	304,254	7,138	4.50x	7,138	1,568,768	1,568,768	1,568,768	1,568,768	1,568,768	1,568,768	1,568,768	1,568,768	1,568,768	
Horiz/Vert Lines	125,064	71,336	1.75x	125,656	71,696	1.75x	173,711	24,371	8.60x	50,042	23,541	2.82x	40,853	9,078	4.50x	9,078	132,637	24,171	24,171	132,637	132,637	132,637	132,637	132,637	132,637	
Rectangles (outline)	92,228	45,844	1.76x	82,632	46,876	1.76x	110,682	15,596	6.69x	32,637	14,932	2.98x	26,817	5,773	4.87x	5,773	5,686	85,769	15,996	15,996	5,686	5,686	5,686	5,686	5,686	5,686
Rectangles (filled)	3,087,003	1,807,456	1.71x	3,122,844	1,816,740	1.71x	4,420,687	570,510	9.96x	1,253,866	584,370	2.04x	1,02,576	23,086	4.69x	23,086	223,509	370,509	370,509	200,509	200,509	200,509	200,509	200,509	200,509	
Circles (filled)	452,728	284,164	1.56x	454,956	285,536	1.59x	492,735	95,606	7.70x	167,564	71,749	2.36x	136,940	28,005	4.51x	28,005	27,596	423,221	95,606	95,606	1,604,480	1,604,480	1,604,480	1,604,480	1,604,480	1,604,480
Circles (outline)	497,252	135,580	3.06x	499,604	136,348	3.07x	432,728	150,413	32.97x	199,266	37,258	5.35x	133,261	15,561	8,566	15,743	404,412	151,143	151,143	404,412	404,412	404,412	404,412	404,412	404,412	
Triangles (outline)	261,054	99,496	4.48x	262,392	98,806	4.48x	225,999	74,899	30.26x	101,480	23,634	4.29x	68,473	16,319	6,636	16,463	21,563	74,899	74,899	74,899	74,899	74,899	74,899	74,899	74,899	
Triangles (filled)	1,130,728	494,456	1.91x	1,137,206	698,032	1.91x	1,432,757	206,598	6,691	429,998	199,995	2.19x	345,244	75,450	4.57x	75,450	1,279,413	209,598	209,598	1,279,413	1,279,413	1,279,413	1,279,413	1,279,413	1,279,413	
Rounded rects (outline)	528,576	100,496	2.28x	250,024	100,532	2.28x	230,767	62,675	11,013	62,280	23,635	3.90x	65,233	9,576	6,812	9,602	200,509	62,732	62,732	200,509	200,509	200,509	200,509	200,509	200,509	
Rounded rect (filled)	3,227,968	1,976,736	1.56x	3,143,588	1,967,193	1.56x	4,294,111	376,880	8.99x	1,227,671	596,202	2.14x	1,02,024	225,027	4.28x	224,252	3,339,751	570,509	570,509	3,339,751	3,339,751	3,339,751	3,339,751	3,339,751	3,339,751	
Fill screen by pixels	1,160,952	918,732	3.66x	1,387,308	921,022	3.66x	2,783,000	1,901,281	3.33x	1,216,214	904,753	2.48x	805,371	229,258	3.51x	199,327	2,364,859	1,591,181	1,591,181	2,364,859	2,364,859	2,364,859	2,364,859	2,364,859	2,364,859	
Fill screen by bitmaps	528,576	95,088	0.61x	531,112	859,520	0.61x	435,257	62,732	0.51x	66,030	526,189	0.12x	70,363	234,904	0.30x	955,075	453,075	62,732	453,075	453,075	62,732	62,732	62,732	62,732	62,732	
Scroll and fill screen	532,988	885,096	0.62x	338,888	860,352	0.62x	439,860	67,668	0.52x	69,357	821,013	0.13x	71,933	258,385	0.39x	366,666	457,046	67,668	457,046	457,046	67,668	67,668	67,668	67,668	67,668	
Min	82,224	45,844		82,632	46,876		99,600	15,596		32,657	14,932		26,817	5,773		5,773	5,686		85,769							
Avg	1,097,348	598,536	1.83x	1,032,854	601,624	1.83x	1,230,188	256,722	4.49x	405,490	233,937	1.73x	316,067	97,446	3.18x	97,446	1,063,867	276,722	276,722	1,063,867	1,063,867	1,063,867	1,063,867	1,063,867	1,063,867	
Max	3,369,952	1,976,736		3,387,308	1,987,580		4,432,987	1,591,381		1,257,871	586,252		1,032,576	235,385		224,252	3,339,751	1,591,181		3,339,751						
Sum	16,460,184	8,976,056		16,545,808	9,024,204		18,751,620	4,150,227		6,061,077	3,506,059		4,551,085	1,461,246		1,461,246	1,252,640		15,948,266	4,150,037						
DrawWithDMA test (drawing of 42 colored numbered circles)																36fps (Unified App)				17.8 fps at CPU 153MHz SPI 27MHz	2.6					
																				46.5 fps at CPU 250MHz SPI 62.5MHz						


Full color PicoDVI test on Raspberry Pi Pico, RP2040-PICO-PC and 5" TFT HDMI 800x480 display



Own project: Green Energy Monitoring Project (2020 – 2022)



Green Energy Monitoring Application ([Https/WSS](https://WSS) multithreaded local/global servers and HTML 5 web client staff)



The project is started as supporting staff for the field installations of the wind turbines. The main idea was to capture weather information synchronously with the data from the wind turbines working at different places on the field where Kintech Engineering's Eol2020 data loggers were installed. In addition a special MPPT controller was planned to operate the wind turbine and/or photovoltaic load. It was developed appropriate instrumentation and methodology for hacking Eol2020 serial protocol. As a result from successful work a new monitoring system was designed. It is based on Secure Web Sockets, Https, Express middleware, Node IPC and consists of Node JS multithreaded local and global servers and HTML 5 client web application. There are plenty of JS libraries responsible for system functioning but some of the most important once used for data processing and visualization are OpenLayers framework & OpenStreetMap interactive maps, Highcharts JS charting framework, Regression-JS, SteelSeries Gauges and Rose Gauges. Captured information from multiply installation sites is stored, processed and visualized in table and chart views. It can be monitored by many users simultaneously and recast later on.






Own project: Listen and play piano - web application for children (2021)

The screenshot shows a web-based piano application interface. At the top, a browser header displays the URL radevs.net/chraudev/projects/kids-proj/piano/index.html. To the right of the address bar are standard browser controls: back, forward, refresh, and download.

The main content area features a musical staff with a treble clef. A series of black circles of increasing size are placed along the staff, starting from the bottom and moving upwards. Above the staff, there is a large green waveform visualization. Below the staff, another green waveform visualization is shown in a rectangular box.

At the bottom of the screen is a piano keyboard. The keys are labeled with letters: W, E, T, Y, U, O, P, I, followed by a colon and a semicolon. The piano keys are colored in a standard black and white pattern. To the left of the piano keys is a control panel for a media player, showing the title "Bach, Toccata and Fugue" and the subtitle "90 3a 42 – Note On". The media player includes standard controls for play, pause, and volume, along with a progress bar.

Own project: Family Multi-Tree web application (2019 – 2020)



FMTree application snapshots with loaded public data for family tree of Vasil Levski

This software is implemented thanks to Data-Driven Documents (d3.js) library, OpenLayers dynamic maps framework, OpenStreetMap foundation & contributors, d3.js timeline chart by Genscape Inc. and many other libraries and demos. It is written with HTML 5, JavaScript, CSS and works well on almost all modern browsers, locally with data file loaded directly and globally via web server over Internet. Private data can be secured by using local files only or protected Internet place. The application uses CSV or JSON formatted data files to present advanced multitree charts. In addition to the chart, interactive world map and timeline are presented as well. An application for converting images to Data URL is also developed to help the users to deal with text only data. Final multitrees can be exported as high resolution images for publishing and/or printing.

Doctoral dissertation: mathematical support, paper and presentation design and work out (2018 – 2019)
Subject: Ethnobotany and ethnopharmacology – ethnobotanical analysis, sustainable use of medicinal plants
in the Rhodopes and testing ethnopharmacological data on the reptile *Potentilla reptans* L. (family Rosaceae)



**ЕТНОБОТАНИКА И ЕТНОФАРМАКОЛОГИЯ –
 ЕТНОБОТАНИЧЕСКИ АНАЛИЗ, УСТОЙЧИВО ПОЛЗВАНЕ
 НА ЛЕЧЕВИ РАСТЕНИЯ В РОДОПИТЕ И ИЗПИТВАНЕ
 НА ЕТНОФАРМАКОЛОГИЧНИ СВЕДЕНИЯ ЗА
 ПЪЛЗЯЩИЯ ОЧИВОДЕЦ *POTENTILLA REPTANS* L.
 (СЕМ. ROSACEAE)**


маг. фарм. Иrena Димитрова Минчева

Научен ръководител: докт. Екатерина Кожухарова, докт.

РЕЗУЛТАТИ Демографски характеристики на информаторите




РЕЗУЛТАТИ Най-често споменаваните растителни видове, според степента на употреба UV




РЕЗУЛТАТИ Устойчиво ползване на лечебни растения в Родопите



Етноботанически проучвания на Балканите




РЕЗУЛТАТИ Употреба на лечебни растения в Родопите




РЕЗУЛТАТИ

Категории заболевания, според броя на споменавания EU



РЕЗУЛТАТИ

Флористично сходство на растителните съобщества в Централни и Източни Родопи, според коефициента на Jaccard



МАТЕРИАЛИ И МЕТОДИ

ЕТНОБОТАНИЧЕСКИ МЕТОДИ

Събиране на теренни данни

- Полуструктуриран интервю
- Аноним метод

СТАТИСТИЧЕСКА ОБРАБОТКА НА ДАННИТЕ

- Стойност за употреба UV = $\Sigma U_i / n$
- Консистентен фактор $JCF = (n_{AB} - n_A) / (n_A - 1)$
- Ниво за достоверност $PI [U] = \alpha_U * 100 / n$
- Коффициент на съдържание на Jaccard $JU [U] = N_{AB} * 100 / (N_A + N_B - N_{AB})$


БОТАНИЧЕСКИ МЕТОДИ

- Флористичен състав и разноговорие на растителните съобщества в областта и ширината на растителност (Балкан Бане, Балкан Балат)

- Флористично сходство на видовите състави в Централни и Източни Родопи


$$JU [U] = N_{AB} / (N_A + N_B - N_{AB})$$

РЕЗУЛТАТИ Най-често споменаваните семейства



РЕЗУЛТАТИ

Сходство на използвани растителни видове по райони, съгласно JU коефициента



МАТЕРИАЛИ И МЕТОДИ

Район на проучването



28 населени места в Централни и Източни Родопи м. юни 2014 – м. септември 2015



Етноботанически данни от теренното проучване EU номограми (пълен и филтриран вариант)



Сравнителен анализ на растителни видове по категории заболевания, според PI фактора



The assistance provided is in the final phase of the preparation of the doctoral dissertation in the field of ethnobotany and ethnopharmacology. It was expressed in the mathematical processing of the data, their presentation as tables and charts, the preparation of the final print out, the design and work out of the printed abstract and the presentation. In addition, a new method for presenting the data in the form of nomograms was proposed and implemented. Assistance in the preparation of several articles was also provided later on.

Work in progress: GPS/LPS solution for EGPR (2015 – 2020)




Rover staff


Base control staff



Mobile EGPR platform with precise positioning and control



High precision positioning based on RTK GPS modules like ZED-F9P of U-blox



The screenshot shows a software interface with two main windows. On the left is the 'Project Explorer' window, which lists files and their contents. A red arrow points to the file 'gps_reader.js'. The code editor window displays the 'gps_reader.js' file, which contains a class definition for 'gpsReader'. A red box highlights several methods and properties: 'listPorts', 'close', 'error/message', 'formatCoordinate/number', 'getCoordinates', 'getData', 'listPorts', 'onCloseHandler', 'onDataTimerHandler', 'onDisconnectHandler/error', 'onErrorHandler/error', 'onLine/line', 'onOpenHandler', and 'portHandler/error, ports'. Another red box highlights the 'latitude' and 'longitude' properties. On the right is a 3D visualization window titled '3D Surface Visualizer'. It shows a grayscale terrain surface with a red vertical line representing the current GPS position. A red callout bubble points to this line with the text 'GPS position (latitude, longitude)'. The status bar at the bottom of the visualization window shows coordinates: 'Lat: 60.000000 Long: 21.000000'. The bottom-left corner of the visualization window also has a red arrow pointing to it.

```
function gpsReader() {
  this.SerialPort = require('serialport');
  this.nmea = require('nmea');
  this.listPorts();
}

gpsReader.prototype.attached = false;
gpsReader.prototype.connected = false;
gpsReader.prototype.latitude = '';
gpsReader.prototype.longitude = '';
gpsReader.prototype.serialPort = null;
gpsReader.prototype.parser = null;

gpsReader.prototype.gpsManufacturer = 'Prolific'; // Supported GPS Manufacturer
gpsReader.prototype.baudRate = 48000;
gpsReader.prototype.delimiter = '\r\n';

gpsReader.prototype.port = '';
gpsReader.prototype.checkDataInterval = 2000; // Check Interval
gpsReader.prototype.listPortsDelay = 5000; // 5s

gpsReader.prototype.lastDataTimestamp = 0;
gpsReader.prototype.dataTimer = null;

gpsReader.prototype.listPorts = function() {
  this.SerialPort.list(this.portsHandler.bind(this));
};

gpsReader.prototype.portsHandler = function(error, ports) {
  if(error) {
    tools.error('GPS list ports error: ' + JSON.stringify(error));
    return;
  }


  var i = 0;
  var length = ports.length;
  var next = null;

```

GPS support for Easy Ground Penetrating Radar based on USB GPS dongle


One of the latest implementations is related to the GPS localization based on a USB GPS dongle and data written in the SEG-Y files. As a consequence of this, the idea of precise positioning was further developed towards the use of RTK GPS based on modules like ZED-F9P of U-blox. The idea of mounting of the GPR on a remote-controlled mobile device was also floated. For better vehicle control stereo camera and FPV Goggles are proposed. The camera vision can be combined with EGPR application view in the Linux box and broadcasted for observation by many people. Optionally the video can be saved for later review.

Work in progress: GPR control solution for EGPR (2015 – 2020)



GPR control simulation (LTspace IV) and measured (TDS 640A) results


The GPR control solution was investigated and couple of implementations were tested. The latest and the best one was simulated in LTspace IV, prototyped and tested with 500MHz TDS 640A oscilloscope. The simple hardware and the good software control implemented on STM32F405 MCU makes it possible to create extremely flexible and really easy controlled GPR even multi frequency one.




Olimex STM32-H405 based GPR control prototype

Work in progress: Multi-frequency solution for EGPR (2015 – 2020)

Схеми на вариант 4 – сандвич от STM32-H405 и 2(3) платки 61x34 mm




Разширителна плата – включена се юни съединителите EXT1 и EXT2 на STM32-H405. RX_EXT (вертикално) и TX_EXT (горизонтално) съединителите се монтират по тисната страна под USB и JTAG съединителите на STM32-H405 съответно.



Плата приемник – включена се юни съединителите RX_EXT (EXT1/2 опц.) на разширителна плата. Антените се монтират по тисната страна под JTAG съединителят на плата STM32-H405.

Алтернативни схеми на вариант 4



Алтернатива плата приемник – Антените са свързани с S&H схемата чрез свръхшироколентов (20-5500 MHz) съгласуващ (50-100 Ohm) трансформатор (балун). За бърз компаратор се попъзва LT1711 (Rail-to-Rail Complementary output, 2 ns Output Rise / Fall time and 4.5 ns Propagation Delay).

Multi frequency GPR solution with dipole antennas (up to 300 MHz) was investigated, implemented and tested. It was found a couple of problems like the quality of the saw tooth signal and big noise in the receiver stage. Nevertheless, mechanical solution was assessed as good enough for the later usage. In addition, a 500MHz semi-elliptical antenna with a resistive load was investigated and evaluated as a very good solution for a 500 MHz GPR. Meanwhile, the possibility of short pulse generation directly from the MCU was explored. Several candidates manufactured by ST Microelectronics were identified like STM32F334 and STM32G474 having timers with picosecond resolution (217ps and 184ps respectively). Both they are Cortex-M4 32-bit MCU+FPU working up to 72 MHz and 170 MHz respectively. The disadvantages are the low performance of STM32F334 and the difficult delivery of STM32G474 chips in small quantities. Other problem that should be solved is the signal amplification to reach required power.

Платки на вариант 4 – размери и оформление




Плата приемник
– стик 1
Със и без монтиран
съединители EXT1/2


Расширителна
плата 2

Плата предавател
Надграждена плата
самостоятелна



EGPR – изглед на стойката и разположение на елементите



Варианти на предавател: 50, 200 и 350 MHz за подземни обекти с диполна антена;
500, 750 и 1000 MHz за подземни обекти с екранирана антена;
1500 MHz за бетон с екранирана антена.






Алтернатива плата предавател – SPI EEPROM и стандартен потенциометър е използван вместо дигитален такъв. Антените са свързани с изхода на генератора чрез свръхшироколентов (20-5500 MHz) съгласуващ (50-100 Ohm) трансформатор (балун). Платката има STM32-H405 EXT конектор за монтаж в общ стик с другите платки.




Алтернативна антена – 500 MHz екранирана полу-елептична антена с резистивен товар

Own project: Easy Ground Penetrating Radar (2015 – 2018)
Complex co-design: Components, interconnections and casing



Two Linux boxes were finally assembled. Serious attention was also paid to the heat transfer in order to prevent overheating of the interior. The software was built and installed. Final long term high load functional tests were executed and finished successfully. The application controller was connected to EASYRAD's GPR and all the system was tested and found to be working as expected. Unfortunately, EASYRAD's GPR was fried at battery charging and collaboration with its developer was discontinued.

Own project: Easy Ground Penetrating Radar (2015 – 2018)
 Complex co-design: PCB, mechanical and casing



PCBs, panels, labels and other staff development (Eagle, AutoCAD and Corel Draw) and production (incl. laser/water cutting)

The complex co-design of all electrical and mechanical components was carefully executed with particular attention to functionality and third-party manufacturability in small quantities on an acceptable price. In design stage was used Eagle, AutoCAD and Corel Draw SW packages. At production were used modern technologies like plastic foil panels, laser, water cutting etc. Serious attention was also paid to the interior and exterior aesthetics without making any compromises with functionality.

Own project: Easy Ground Penetrating Radar (2015 – 2018)

Investigation of hardware reliability with long term high load functional testing methodology

CPU, PMU and battery power and temperature characteristics of A20-OLinuXino-LIME2-eMMC (HW rev. E) based embeddable system

General conditions:

- The board is mounted in 160x165x51.5 mm aluminum box with 15mm thick aluminum thermo-conductor (cooler);
- The cooler contacts to all chips via thin (less than 1.5 mm) thermal pads (6 W/mK) and to the box wall via ARCTIC MX-4 thermal compound (with carbon micro-particles);
- Measurement is done with RPI Monitor on Armbian 5.12 with U-Boot 2016.5 and Linux Kernel 4.5.5 under application test load for whole discharge / charge cycle.

Note: The higher voltage drop problem at the first test was solved with changing the power wires with proven quality 18 AWG once.

High load test conditions:


- Stress tests: (while true; do stress -c 1 -i 1 -t 600 done);
- Network performance test: iperf -s + (while true; do iperf -c GBIT_IP done) on i7/Windows 7/VMWare 8/Ubuntu 14 LTS box
- Application test: node.js server (started from rc.local) + JS client running in Chrome browser on i7/Windows 7 box

Notes: stress and server side iperf test staff was started from ssh consoles from PuTTY on i7/Windows 7 box.

CPU total load (as reported by RPI Monitor): 4.4 – 5.9 (1 min averaged), 5.1 (15 min averaged)



High temperature test conditions:

- All staff was put in a thermally isolated chamber (300 x 240 x 120 mm);
- Automotive 12 V / 21 W lamp and manually regulated power supply was used to heat the chamber air (dissipated power by device 2.5 W and 11.5 W additional);
- Computer 12V ventilator was used to homogenize the chamber air;
- First DS18B20 sensor and standalone digital thermometer were used to measure the chamber air temperature;
- Second DS18B20 sensor was mounted on the aluminum thermo-conductor (cooler);
- PMU and CPU temperatures were measured by armbianmonitor middleware.



Investigation of hardware reliability was done with long term high load functional testing methodology applied mainly to the Linux box based on A20-OLinuXino-LIME2-eMMC (HW rev. E). It was found problems with the heat transfer causing interior overheating and system crashes. That is why metal case was chosen and special passive cooling system was designed and tested. Massive heat-conductor was used to take away the heat from all hot chips on the board to the case. Thermal paste and a special thermal self-adhesive film, both with high quality, were used to improve the contact with the chips and the case.

Own project: Easy Ground Penetrating Radar (2015 – 2018)
Reapplied: Complex co-design and Long term high load functional testing methodology



It was started common project for development of flexible and contemporary GPR platform in cooperation with EASYRAD, developer and producer of series of such devices. It was planned that the mechanical design and analog components would remain as they were originally, but the digital ones had to be developed from scratch. Distributed architecture was chosen based on STM32F405 MCU/ChibiOS for the real time tasks, A20-OLinuXino-LIME2-eMMC/Linux for the server staff and tablet or laptop with any OS for the client staff. Software is planned to be written on C, JavaScript and HTML 5 and to be based on Secure Web Sockets, Https for both server and client staff. Single and two dimensional Local Positioning System (1D/2D LPS) and 2D/3D visualisation would also be a part of the future development. Production and sales prices can double at most.

How To projects (2015 – 2020)

Development, testing, documenting: Written documentation and references

Armbian customization how to

Armbian

Ubuntu/Debian images for ARM based single-board computers: <http://www.armbian.com>

Armbian main links

- Linux for ARM development boards
- Basic Documentation
- Advanced Documentation
- Armbian build tools on Git

Armbian Forum Links

- Armbian customization - main thread
- Add support for A20-OlinuXino-Lime2-eMMC
- Olinex Lime A20 Want boot armbian
- Added Lime2 eMMC support
- Testers wanted: some adjustments for RPi-Monitor
- [Wi-Fi] aap209 mainline sysfs interface

Olimex Forum Links

- A20-OLinuXino-LIME2 new HW Rev. E
- How to use eMMC on A20-OLinuXino-LIME2-eMMC
- Extremely slow Ethernet on A20-OLinuXino-LIME2
- OlinuXino A20 Lime 2 problems

Linux SUNXI User Group

- [PATCH 1/1] ARM: dts: sunxi: Add a olinuXino_lime2_eMMC
- USB OTG on A20 Lime2 board does not work with mainline kernel
- [PATCH] sunxi: sunxi: Ignore VBus errors in host-only mode
- [PATCH 07/15] sunxi: Add support for the Allwinner sunxi sunxi controller

Our projects SVN links

- GPR Linux
- GPR Node JS
- GPR Web
- GPR Armbian

How to build Armbian (official notes)

Preparation

- x86/x64 machine running any OS; 4G ram, SSD, quad core (recommended),
- VirtualBox or similar virtualization software (highly recommended),
- alternatively - Docker, systemd-nspawn or other containerization software,
- compilation environment is highly recommended to be Ubuntu Trusty 14.04 or Ubuntu Xenial 16.04 (other releases are **not officially supported**),
- installed basic system, OpenSSH and Samba (optional),
- superuser rights (configured `sudo` or root shell).

Execution

```
apt-get -y install git  
git clone https://github.com/ignpersson/lime --depth 1  
cp lib/compile.sh .  
./compile.sh
```

376 lines (2015)


Armbian customization details

The target of customization described is to get production ready Armbian build for A20-OlinuXino-Lime2-eMMC board complying with user defined requirements.

Armbian customization requirements

- Usage of main Armbian code base without modification
- Build process has to be non interactive and capable to be automated
- All customization stuff has to be:
 - delivered from own repository
 - applied mainly at the build process
 - only limited actions (preferably none) can be finished at the first run
- Final firmware has to be capable to be:
 - delivered to the user as a single file (as small as possible)
 - self sufficient and closed (not allowed later package updates)
 - updated on the field easily and with minimal user assistance
 - restored easily after any system crash
- The system has to:
 - function autonomously from the very beginning
 - be stopped and (re-)started with a single button touch
- User will interact with the system only via
 - the web interface
 - a limited number of buttons and LEDs
- Additional user hardware has to be connected via available interfaces:
 - 2x USB Host and 1x USB OTG
 - 1x GBit native LAN
 - SATA and others bringing out GPIO connectors
 - Serial console will be used for development, production and maintenance only
 - HDMI and USB keyboard can be used in development process optionally as well
- Following HW will be attached to the system permanently:
 - Li-Po battery granting long life time and charged via DC-IN connector
 - eMMC containing fully functional and read only spare copy of the system
 - SATA SSD containing system and user data
 - USB Wi-Fi Adapter working in "Access Point" mode
 - user buttons, LEDs and edge connectors
 - fully hermetic metal case with water proof edge connectors and controls
 - efficient cooling system taking off the heat via case walls
- Following HW will be attached to the system optionally on demand

CPU, PMU and battery power and temperature characteristics of A20-OlinuXino-LIME2-eMMC (HW rev. E) based embeddable system



763 lines (2015)

How to make MacBook Pro (15-inch, Late 2008) and iPad 2 useful in the year 2020

This blog is written to express my gratitude to all the people helped me to fulfill this initiative

Here one can find the steps for hardware upgrade of MacBook Pro (15-inch, Late 2008) and installation on it and iPad 2 the latest supported by Apple Mac OS X v. 10.11.6 El Capitan, iOS v. 9.3.5 and MS Windows 10. All the steps made took more than a month reading, testing, more than 6 hours phone talks with Apple Support and as an exception tens of e-mails. More than 5 friends of mine were also involved in this tedious battle.

On the other hand because of our ignorance of contemporary Apple hardware and software some of the problems were definitely provoked by me. Some of the obvious facts written in this blog are also a consequence of the lack of knowledge and experience so be indulgent.

1. Hardware upgrade

- The main hardware of MacBook Pro (15-inch, Late 2008) is:
 - Intel Mobile Core 2 Duo CPU P8600 @ 2.4GHz
 - RAM 4GB DDR3 @ 1066MHz and 230pin SATA I HDD
 - 250GB NVIDIA GeForce 9400M GT Graphics
 - 15.4-inch, 1440 x 900 pixels LCD with 32-bit color
- Additional but helpful hardware of MacBook Pro (15-inch, Late 2008) is:
 - Gigabit Ethernet connector – preferable to Wi-Fi better as speed and reliability
 - Dual USB 2.0 and Firewire connectors – useful to connect external devices

1.1. Repairing of MacBook Pro (15-inch, Late 2008) and some workarounds

- One big trouble was that the battery fails and has to be changed
- At the same time failed capacitor on the motherboard makes a trouble trigger
- After changing the battery and repairing MacBook become ready for upgrade
- It is useful to know that MacBook Pro (15-inch, Late 2008) can work without battery
- One more problem was failed internal DVD device and has to be used external one connected via USB
- Unfamiliar language specific keyboard can also be a problem so it can be used additional one via USB
- The problem at using unfamiliar keyboard in passphrase entering when the chars are not shown at all
- Some special characters can also be a problem to be entered even at visible fields

1.2. Changing memory from 4GB to 8GB

- It can be upgraded up to 8GB (there are some modules recommended)
 - https://eshop.mackableres.com/guides/Mac_Os_X_Compatibility
- 1.2.1. Search and buy 2 modules 4GB DDR3, 1.3V, 1666 or 1333 MHz
- 1.2.2. Modules have to be the same type and from the same manufacturer
- 1.2.3. Modules can be from different manufacturers but with the same parameters
- 1.2.4. Test them with current software installation
- 1.2.5. Successfully used 4GB DDR3 1333MHz different modules:
 - Samsung, PC3-10700 (667 MHz), Part Number M471B273CH9-CH9
 - Kingston, PC3-10700 (667 MHz), Part Number 9905420-001.A00LF
- 1.2.6. Do not install them before complete new software installation

1.3. Changing internal HDD with SSD

- It can be upgraded up to 4TB internal HDD or SSD (there are some devices recommended)
 - https://eshop.mackableres.com/guides/Mac_Os_X_Compatibility
 - https://evermact.com/systems/apple/macbook_pro/macbook_pro-13-15-17-mid-2009-how-to-upgrade-hard-drive-ssd.html
 - <https://www.eastonsoft.com/Answers/View/142374/What+mu+the+macintosh+size+hard+drive+I+can+put+in+my+Mac+2009+MB+Pro>
 - <https://www.klootgeek.com/article/323249/can-youUpgrade-the-hard-drive-to-ssd-in-your-mac/>
 - <https://www.macsolid.com/article/323249/can-old-macbooks-compatibility.html>
- 1.3.1. Original HDD: Hitachi HTS725032L9SA0, 250GB, 5400RPM, 2.5" (BA37325) SATA I (150Mbps)
- 1.3.2. For cheaper 400GB SSD with option to return in case of incompatibility
- 1.3.3. Take in account that MacBook Pro (2.4 GHz, 15-inch, Late 2008) has SATA II controller
- 1.3.4. It could be incompatible with some SSDs especially expensive and fast ones
- 1.3.5. There is indication that Adata, Crucial and Kingston SSDs may work
- 1.3.6. Successfully used 447GB Crucial CT40BX300SSD1 ATA Device (SATA (SSD))
- 1.3.7. Do not install it before preparation of the software installation

2. Installation of MacBook Pro for dual boot of Mac OS X and Windows 10

- There is no official Apple support for Windows 10 as Boot Camp and drivers for old MacBooks
- Fortunately, all drivers for MacBook Pro (2.4 GHz, 15-inch, Late 2008) are available from Internet
- Successfully updated after Windows installation by Snappy Driver Installer Origin
- The only problem is multi touch driver but there is an overcome procedure (not tested)
 - <https://discussions.apple.com/thread/7167021>


405 lines (2020)

An own Linux distribution is planned for EGPR project so investigation about appropriate building platform was started. Armbian was chosen and evaluated. While studying customization details around A20-OlinuXino-LIME2-eMMC/Debian and adapting it to project requirements series of How-To notes were described. As a result, all notes and progress were documented and shared. Many aspects including results of long term high load functional testing were discussed in corresponding forums. Later on while MacBook Pro (15-inch, Late 2008) laptop and iPad-2 tablet were refurbished and improved all notes and progress were also described and shared as a How-To document.


Advanced embedded projects (2015 – 2018)




Olimex STM32-E407



Eclipse C project





Web sockets staff




Performance measurement report


Advanced HTTP(S) and Web Sockets solution for embedded devices based on STM32F407 with Ethernet and ChibiOS




Olimex STM32-H405 & USB3300



STM32Cube/Eclipse C project



Application staff




Performance measurement report


Advanced High Speed USB communication solution for embedded devices based on STM32F405, ULPI, USB3300 with STM32Cube and FreeRTOS

With respect to the forthcoming EGPR project HTTP(S) and Web Sockets services solution for embedded devices based on STM32F407 with Ethernet and ChibiOS was implemented and evaluated. Software implementation was very close to the real project requirements and series of measurements was made. Performance result was assessed carefully and the solution was rejected. For increasing of communication throughput USB high speed solution based on Olimex STM32-H405 & USB3300 ULPI chips are tested. The results were much better than at LAN scenario but other staff was limiting again so STM32F405/ChibiOS, A20-OLinuXino-LIME2-eMMC/Linux solution was chosen.

Advanced embedded projects – continue (2015 – 2018)




ChibiOS demo on STM32-H405: USB cdc, adc, dac, pwm, tim, MCP4xxx, Rot. enc. etc.




STM32Cube demo on STM32F4-Discovery/STM32-E407: USB Host, multi profile

Series of advanced embedded projects were developed while studying and evaluating Cortex-M4 MCUs like STM32F405/7, Olimex STM32-H405, STM32-E407 and ST STM32F4-Discovery boards were used as hardware. Eclipse CDT, ChibiStudio, ChibiOS, STM32Cube, FreeRTOS and other mainly open source packages and libraries for Windows, Linux and MacOS were used as software. Big number of open source projects and demos were also used to build and evaluate really advanced embedded projects. All they were developed, discussed and shared with other people.



STM32Cube demo on STM32-E407: a-test




ChibiOS demo on STM32-H405: b-test

How to operate STM32Cube and CubeMX based projects in unified environment composed by free and open source tools only

Project targets and references

well tested and documented a/b-tests



STM32Cube based demo for STM32F4-Discovery: USB Host, R/W files on MSC

Helpful software projects (2015 – 2017)




DS18B20
Digital Resolution

1-Wire Digital Thermometer

- User-Definable Nonvolatile (NV) Alarm Settings
- Address-Searched Command Identifier and Address-Device Whose Temperature is Outside Predefined Limit (Temperature Alert Condition)
- Available in 3-Pin SO (150 mAh), 8-Pin TSSOP, and 1-Pin TSOP-32 Packages
- Software Compatible with the DS18H22
- Applications Include Thermocouple Controls, Industrial Systems, Consumer Products, Thermometers, or Any Thermally Sensitive System

PIN CONFIGURATION



1-800-541-2238 • www.msi.com • www.msi.com/MSI

Dallas 1-Wire Digital Thermometer

Digital Potentiometer Solutions

Microchip's Family of Digital Potentiometers

Microchip offers a wide range of devices that allow you to select the best fit for your application needs. Some of the selection options include:

- End-to-end resistance (fixed values - 2.5 kΩ to 100 kΩ typical)
 - Resistors
 - 100 ohm steps
 - T-tail (128/129 steps)
 - 8-bit (256/257 steps)
 - Serial interfaces
 - I₂C/SMBus
 - SPI
 - PCF
 - Memory types
 - Volatile
 - Resistor networks configurations
 - Potentiometer (voltage divider)
 - Rheostat (variable resistor)
 - Single, dual, and quad potentiometer options
 - Differential potentiometer options
 - Special features
 - Shutdown mode
 - Wakeup™ technology
 - Low voltage options (3.3V)
 - Low voltage options (1.8V)
 - High-voltage options (36V or ±180V)

Microchip offers digital potentiometer devices with typical end-to-end resistances of 2.1 kΩ, 5 kΩ, 10 kΩ, 50 kΩ or

The serial interface options allow you to easily integrate the device into your application. In some applications, the simple

The serial interface options allow you to easily integrate the device into your application. For some applications, the simple up/down interface will be adequate. Higher-resolution devices (Tekt, Biotek) often require direct read/write to the xeror.

[View more](#)

Microchip Digital Potentiometers

Dallas 1-Wire Digital Thermometers and Microchip Digital Potentiometers were rated as very useful devices for many use cases. Therefore, extensive research was done to find good software libraries and projects supporting these devices. Unfortunately, the resources found did not satisfy our requirements, so we decided to make our own implementation. Of course, the found projects are used and we respect their authors. Both projects were shared and used later on in other projects we worked on.

```

#include "OneWire.h"
#define OneWire_h

#include <iostream.h>
#include "Wire.h"

#define FALSE 0
#define TRUE 1

class OneWire {
private:
    uint8 pin_DQ;
    // global search state
    unsigned char ROM[8];
    uint8 last_discrepancy;
    uint8 done;

    uint8 readScratchpad(unsigned char *deviceID, unsigned char *scratchpad);
    uint8 writeScratchpad(unsigned char *deviceID, unsigned char *scratchpad);
    uint8 copyScratchpad(unsigned char *deviceID);
    uint8 getResolution(unsigned char configByte);
    void writeByte(unsigned char byte);
    void writeBit(uint8 bit);
    unsigned char readByte();
    uint8 readBit();
    int touchByte(int byte);
    void block(unsigned char *data, int data_len);
    void select(unsigned char *deviceID);
    int crcl(unsigned char *deviceID, int length);
    int reset(void);

public:
    OneWire(uint8 pin);
    void resetSearch();
    uint8 search(unsigned char *deviceID);
    uint8 readPower(unsigned char *deviceID);
    uint8 readPower();
    uint8 broadcastConvertTemperature();
    uint8 convertTemperature(unsigned char *deviceID);
    uint8 convertTemperature();
    uint8 setResolution(unsigned char *deviceID, uint8 resolution);
    uint8 setPermanentResolution(unsigned char *deviceID, uint8 resolution);
    uint8 getResolution(unsigned char *deviceID);
    float readTemperature(unsigned char *deviceID);
    float readTemperature();
};

#endif

```

C++ Library

Arduino example

```

/*
 * HCD4XXXX.C
 *
 * Created on 17.09.2012 14:
 *      Author: Meister
 */
#include "mpuscan.h"

/*
 * API for serial buffers.
 */
static uint8_t value[2];
static uint32_t index[2];

void mpuscanInit(mpuscanDevice *dev)
{
    dev->api->init(dev);
}

/*
 * Register function
 */
void mpuscanRegister(mpuscanDevice *dev, uint8_t address, uint8_t data, uint8_t isLastValue)
{
    value[0] = HSC4XXX_OBD_WRITE | address;
    value[1] = data;

    // Calculate the 4-Bit data value to send
    if(data > 255)
        value[0] |= 0x0000_0001;

    dev->api->sendRegisters(2, value, index);

    if(!isLastValue)
        // EEPROM write cycles take one each. So we block with delay(1) after any 100 writes
        dev->api->sleep(50);
}

return (data & index[0]) >> 8;
}

uint8_t mpuscanReadRegister(mpuscanDevice *dev, uint8_t address)
{
    value[0] = HSC4XXX_OBD_READ | address;
    value[1] = 0xFF;

    dev->api->sendRegisters(2, value, index);

    return HSC4XXX_OBD_REGISTER_VALUE + (value[1] & index[0]) << 8 + (value[0] & index[1]);
}

```

Own project: Powerful wind generator and test suite (2014 – 2016)

Reapplied: Complex co-design and Long term high load functional testing methodology





Generator Construction



Generator Implementation




Generator Improvements



In addition to the described achievements, a prototype of a powerful (10 kW) DC/CD Up/Down converter was developed but not tested yet. Two generators were produced as prototypes. Two pilot installations were also made (high-speed spiral turbine at 1860 m altitude near the Belmeken dam and low-speed turbine with H-Blades at 64 m altitude near the town of Shabla). A couple of proposals for starting of generator production were also made but not accepted yet.

Own project: Powerful wind generator and test suite (2014 – 2016)




Long term high load functional testing methodology: generator and full-featured test suite





In addition to the selected generator, a test bed was also developed. Both the generator and the test bed underwent a series of modifications and even a complete redesign, but in the end a maximum power more than 5 kW was reached. Some of the successes include two variants each of the stator (melted and milled), the rotor (with massive and lightweight hub) and the coils (60 and 120 turns). The test bed in its second version was redesigned from scratch, and the drive went from a DC motor to a high-frequency AC one controlled by a special controller and powered by storage batteries. Three variants of the load resistor (DC with manual and electronic control, as well as three-phase AC) were also developed. Several variants of the electronic data collection system and off-line data processing methodology were developed and used as well.

Own project: Powerful wind generator and test suite (2014 – 2015)

Complex co-design: 2D/3D dynamical electromagnetic and 3D mechanical modelling



3-phase generator with axial flux ironless topology and permanent magnet excitation – modelled in 3D Maxwell and 3D AutoCAD Mechanical



3-phase generator with concentrating transverse flux topology and permanent magnet excitation – modelled in 2D FEMM and 3D AutoCAD Mechanical

An own project for development, production and installation of small wind turbines was stared. First idea was to develop vertical spiral turbine and 3-phase generator with concentrating transverse flux topology and permanent magnet excitation. Later on, because of technological consideration 3-phase generator with axial flux ironless topology and permanent magnet excitation was chosen. All ideas were subjected to careful analysis and modelling both electro dynamically and mechanically. Final solution for the generator was to use strong NdFeB wedge permanent magnets for reaching 5 kW maximal power. For the turbine the estimation was to use static wings for increasing the wind power.

Own project: Arduino like staff based on STM32F1/4 and ChibiOS/STM32Cube (2014 – 2015)

@rtino


MCU Boards:

- Micro 60x37
- Mini 60x60
- Midi 80x60
- 60x80
- Maxi 80x80

Main Boards:


- Micro 60x60
- Mini 80x60
- 60x80
- Midi 80x80
- Maxi 100x80
- 80x100

User Button / LED
Power / Activity LEDs
USB OTG Full / High Speed
SD/MMC (SDIO/SPI)
Ethernet Connector
Reset Button
Power Jack





All MCU parts A...I (0...15)
extensible in vertical direction
Display Ext – 3.7 QVGA with Thouchscreen



Other boards:
STM32-LCD – dedicated MCU + 3.7" LCD
IMX233-OLinuXino / Mini – 454MHz ARM926J
A13-OLinuXino-MICRO – 1GHz Cortex A8
A13-LCD7-TS – Innolux 7" (480x800) display



Advanced solution proposal: NFC and Linux based Internet enabled Access Control System (2013 – 2014)






Embedded Linux with OSGI services and NFC card reader



Open source staff, application interface and performance tests


As a result of gained experience in the field of Internet enabled access control systems a proposal for migration to a new architecture was suggested. The main idea is to use NFC and Linux as a base for a new generation of intelligent card readers building ed hoc distributed system. Proposed solution was feasible because of great decreasing of the prices and the consumption of the Linux capable SOCs and can give extremely high level of flexibility and scalability avoiding power hungry server staff and intermediate infrastructure. Unfortunately, proposed solution did not gain popularity because security companies are very conservative and not opened for technological novelties especially open source based.




Prototypes based on open hardware, Arduino like and Olimex development boards

A number of MCU based development and open hardware boards were explored and evaluated for usage in various projects. Some were part of popular Arduino ecosystem, but others were for professional use like header and development boards from Olimex and other companies. Some prototypes were also made. Besides the MCU staff, many Linux capable SOCs and corresponding boards were also part of the devices used, including in combination with MCUs for splitting the real time and the processing hungry tasks.

RISCO: RFID card reader for Internet enabled Access Control System (2011 – 2014)
Reapplied: Long term high load functional testing methodology



A developer's desk for HW/SW co-design, development and testing in common



Inheriting the project for RFID card reader for Internet enabled access control system in a rather initial phase and without support especially in the area of testing, a new and different methodology was introduced combining the development and the testing in a common process. Long term high load functional testing methodology was accepted as a base and a special test suit including real infrastructure and complete server staff was developed, implemented and continuously used for massive testing of devices in real use case. This approach allowed all errors in the hardware and software, including those in the supporting infrastructure and server staff, to be immediately detected and fixed in the development process. Other big success was recognition by the firmware of different production variants (RS232, RS485 CAN) and ability to adapt silently.

Development, documenting, testing: Written documentation, examples and references

Building and setup Ångström distribution from scratch

Host platform: [Ubuntu Desktop 10.10](#)

Target platform: [Olimex CS-E9302 Development board](#)

1. Overview

Ångström was started by a small group of people who worked on the OpenEmbedded, OpenSaurus and OpenSmpad projects to unify their effort to make a stable and userfriendly distribution for embedded devices like handhelds, set top boxes and network-attached storage devices and more. All Ångström binaries are built using [OpenEmbedded](#).

OpenEmbedded offers a best-in-class cross-compile environment. It allows developers to create a complete Linux Distribution for embedded systems. Some of the OpenEmbedded advantages include:

- support for many hardware architectures
- multiple releases for those architectures
- tools for speeding up the process of recreating the base after changes have been made
- easy to customize
- runs on any Linux distribution
- cross-compiles 1000's of packages including GTK+, Qt, the X Windows system, Mono, Java, and about anything else you might ever need

Bitbake handles the parsing and execution of the data files. The data itself is of various types; recipes which give details about particular pieces of software, class data which is an abstraction of common build information (e.g. how to build a Linux kernel) and configuration data for machines, policy decisions, etc., which acts as a glue and binds everything together. Bitbake knows how to combine multiple data sources together, each data source being referred to as a layer. Bitbake is responsible for parsing the metadata, generating a list of tasks from it and then executing them. The most common usage is **bitbake packagename** where packagename is the name of the package you wish to build (from now on called the target). This often equates to the first part of a .bb file, so to run the simple-**package_1.2.3.bb** file, you might type **bitbake simple-package**. Several different versions of **simple-package** might exist and bitbake will choose the one selected by the distribution configuration. Bitbake will also try to execute any dependent tasks first so before building **simple-package** it would build a cross compiler and glibc if not already built.


The **Metadata (recipes)** are .bb files that are usually referred to as 'recipes'. In general, a recipe contains information about a single piece of software such as where to download the source, any patches that are needed, any special configuration options, how to compile the source files and how to package the compiled output.

Class (.bbclass) files contain information which is useful to share between metadata files. An example is the autotools class which contains the common settings that any application using autotools would use.

The **configuration (.conf)** files define various configuration variables which govern what Poky does. These are split into several areas, such as machine configuration options, distribution configuration options, compiler tuning options, general common configuration and user configuration (local.conf).

54 pages (2011)

Среды для разработки в проекте Yocto



When working with a student on his thesis number of How-To documents was written for different aspects of the corresponding projects like the process of building and setting up Ångström distribution from scratch, installing ChibiStudio and Eclipse as development IDE on different OS platforms, usage of ChibiOS for real time embedded projects. One of the very useful documents was description of how to operate STM32Cube and ChibiOS based projects in unified environment composed by free and open source tools only.

How to install ChibiStudio and use ChibiOS on Windows machine

At the date (Mar 27, 2015) of writing following ChibiOS and ChibiStudio (<http://chibios.org/>) versions are available for download from (<http://sourceforge.net/projects/chibios/>) and SVN (<http://svn.code.sf.net/p/chibios/svn/trunk/>) and Git (<https://github.com/ChibiOS/ChibiOS-RT>) repositories:

- Stable ChibiOS/RT ver. 2.6.7 (<http://sourceforge.net/projects/chibios/files/ChibiOS%20RT%20Stable/Version%202.6.7/>)
- Development ChibiOS/RT/NIL ver. 3.0 (<http://svn.code.sf.net/p/chibios/svn/trunk/>)
- Contributor's stuff for ChibiOS/RT/NIL ver. 3.0 (<https://github.com/ChibiOS/ChibiOS-Contrib>)
- ChibiStudio Preview 9 (http://sourceforge.net/projects/chibios/files/ChibiStudio/ChibiStudio_Preview%209/)

The easiest way to start is to install ChibiStudio Preview 9 containing both ChibiOS/RT ver. 2.6.7 and ver. 3.0 dev versions. Unfortunately, included Eclipse version Luna is for 32-bit Windows and will not work on a 64-bit host. To overcome this problem Eclipse IDE for C/C++ developers for Windows 64-bit has to be installed. This is tested on Windows 7/8 and it is applicable for newer Eclipse versions as well. Installation is also tested on VMWare Workstation with Windows 8 guest and work fine but there are problems with FW upload via ST-LINK/V2 Utility. There is also problem to connect USB removable devices (Virtual com ports for example) when connected via some USB 3.0 ports of the host machine. There is not possible to move USB device to the VM when it is wrong enumerated. That is why installation on real Windows machine is recommended.

Description of main procedures required for successful startup:

1. Download ChibiStudio last version and unzip it in C:\ChibiStudio\;
2. Install the drivers for JTAG/SWD adapter (ST-LINK/V2) including STM32 ST-LINK Utility;
3. It is good idea (for make from command prompt) to add to the Windows PATH variable following folders:
 - a. C:\ChibiStudio\tools\gnatools\bin and
 - b. C:\ChibiStudio\tools\GNU Tools ARM Embedded\4.7 2014q2\bin;
4. Try to run it using following steps in \readme.txt and if it start skip next step;
5. Install and prepare latest Eclipse IDE for C/C++ developers for Windows 64-bit:
 - a. Download Eclipse IDE from <http://www.eclipse.org/download/>;
 - b. Rename C:\ChibiStudio\ eclipse to C:\ChibiStudio\ eclipse-32bit;
 - c. Unzip Eclipse IDE zip file to C:\ChibiStudio\ eclipse;
 - d. Run it and install following plugins (work with All update sites):
 - i. Add new update site embsysregview - <http://embsysregview.sourceforge.net/update/>;
 - ii. Eclipse XML Editors and Tools 3.6.3;
 - iii. Embedded Systems Register View plugin 0.2.3;
 - iv. EmbSysRegView Data plugin 0.2.5.r180;
 - v. Target Management Terminal 3.7.0 (Deprecated) incl. RxTx Serial Connector plugin;
 - e. Install ChibiOS/RT plugins and features (use update site for latest versions if found):
 1. (org.chibios.*)" from \eclipse-32bit\plugins\{to\|eclipse\|dropins\}eclipse\plugins\4\plugins\;
 2. (org.chibios.*)" from \eclipse-32bit\features\{to\|eclipse\|dropins\}eclipse\features\4\feature\;
 - f. Run ChibiStudio:
 - i. Choose for Workspace one of the existing ones (\workspace26 or \workspace30) or make new one;
 - ii. In case of using existing workspaces all demo and test projects will be available in Project explorer ready for build and usage;
 - iii. verify that all above plugins and features are available (Menu > Help > About Eclipse > Installation Details);
 6. Add new ChibiOS version (from trunk for example):
 - a. Open <http://sourceforge.net/p/chibios/svn/HFAD/rev/trunk/> and Download Snapshot;
 - b. Unzip it in \Chibios\0c20150327 for example;
 - c. Open <https://github.com/ChibiOS/ChibiOS-Contrib> and Download Zip;
 - d. Unzip it in \Chibios\0c20150327\community;
 - e. Unzip fafs-0.10b-patched.7z and hwp-1.4.1_patched.7z files in \chibios\0c20150327\community\ext\;
 7. Add, build and deploy existing project from ChibiOS/RT Demos in new and empty Workspace
 - a. Change once following global preferences (from Menu > Window > Preferences):
 - i. General > Workspace > Build automatically (uncheck);
 - ii. C/C++ > Code Analysis (uncheck all problems);
 - iii. C/C++ > Debug > EmbSys Register View set Architecture: cortex-m4, Vendor: STMicro, Chip: stm32f40s, Board: none or one from the list (STM32F4Discovery only for the moment);
 - iv. C/C++ > Project Wizard > Makefile Project > Discovery Options > Automate Discovery paths and symbols (uncheck);
 - b. In Project Explorer > Popup Menu > Import ... > General > Existing project into Workspace > Next > Select root directory > Browse > C:\ChibiStudio\chibios\demos\ARMCM4-STM32F407-LWIP-EATFS-USB > OK where chibios can be one of the existing ChibiOS versions (stable 2.6.7, unstable 3.0 or 3.0 trunk) resided in C:\ChibiStudio folder;

2 pages (2015)



How to operate STM32Cube and ChibiOS based projects in unified environment composed by free and open source tools only

Project targets and references

The project target is to:

- Build combined application code base with ChibiOS and STM32Cube incorporating
 - USB CDC Host to Serial adapter like functionality
 - USB CDC Device to Serial adapter like functionality
 - USB vendor specific Host CDC like classes for CP210x and FT232R adapters
 - USB vendor specific Device CDC like emulation of CP210x and FT232R adapters
 - Performance testing and application debugging staff
- Create development environment based on Eclipse CDT, GNU Arm and Makefiles
- Test a way and describe the path
 - for doing above from the scratch
 - using only free and open source tools and code base

Startup references:

- Eclipse IDE and community projects <http://www.eclipse.org/>
- GNU tool chain for ARM Cortex-M/R processor <http://launchpad.net/gcc-arm-embedded>
- GnuWin32 libraries and management tool for Windows <http://www.gnuwin32.sourceforge.net/>
- ChibiStudio, ChibiOS, its demos and community stuff from <http://chibios.org/>
- STM32Cube application completely generated by STM32CubeMX for STM32-E407 board from <http://www.st.com/web/catalog/tools/EMI47/CL1794/SC061/SS1743/PE259242?ref=mcexplorer>
- Experience to create from scratch Eclipse based environment for ChibiOS
- Makefile based sample project for STM32-E407 board from <http://wunderkis.de/gn32cfc/index.html>
- Demo projects including all described implementation
 - at the moment ab-test.mr, attest-1test, attest-2tar and ab-tests-howto.edif (this file)
 - can be downloaded from <http://www.eudev.net/~wunderkis/ab-test/>



Project stages done:

- Created development environment - single installation to work with:
 - Eclipse Mars CDT 32-bit version on Windows 7 with Java JDK 1.8 both 64-bit versions
 - installed Eclipse IDE for C/C++ developers with Mylyn integration
 - added plugins: STM32CubeMX, GNU Arm C/C++, ChibiOS, EmbSysRegView, TM Terminal, RxTx, SVN etc.
 - tested and tuned global and project settings to work with STM32CubeMX, GNU Arm C/C++ and ChibiOS
 - GNU tool chain from ARM Cortex-M/R MCUs from Launchpad for Windows version 150626
 - GNU tools from ChibiStudio, binutils GnuWin32 complete set, QEMU, OpenOCD ver. 0.9, UVICview etc.
- Created ChibiOS project based on STM32 Cube DCM for STM32-E407
- added board support for STM32-H405 to ChibiOS STM32 based boards
- ChibiOS USB CDC Demo for STM32-E407 ported to STM32-H405
- Created STM32CubeMX project based on STM32-E407 IOC file from wunderkis.de
 - added all peripherals support and F4PFS, FreeRTOS and LWIP middleware
 - integrated Makefile file to generate project code base from wunderkis.de
 - tuned to fit complete STM32-E407 board specification
- STM32Cube application completely generated by STM32CubeMX for STM32-E407 board
 - created and tested basic application without any application implementation
 - added standard IO redirection to USART for debugging
 - added floating point support using STM32 FPU
 - tested multi-device support (CDC and MSC Host classes)
 - tested a way and added more FreeRTOS tasks
 - extended STM32Cube based project with USB Host CDC to Serial functionality
 - added a simple bidirectional data transfer between USB Host CDC and USART
 - added support and measured bandwidths with ChibiOS application on STM32-H405 board
 - extend STM32Cube based project with USB Device CDC functionality
 - added transmitter simulating massive data stream from USB HS CDC Device to USB FS CDC Host
 - added code to calculate and print test statistics
- Make performance tests for throughput, packet utilization and data loss
 - throughput is measured at different buffer sizes, without and with UART and at different UART bitrates
 - packet utilization is measured as 100% in case of sending buffer with size proportional to packet's one
 - there is no data loss measured as a difference between data sent by USART and retransmitted by USBHS sides

How to operate STM32Cube and ChibiOS based projects in unified environment composed by free and open source tools only

1




17 pages (2015)



OSGi базирана разпределена сензорна система





The spots of openness influenced the work




GMD Ltd.: VLF Metal detector based on Mega128/uSmartOS with gLCD/GUI (2010 – 2011)


Development, programing, testing, introduction: Embedded hardware and software implementation





GUI (Graphics User Interface) description



MMI (Machine/Man Interface) description





Firmware start up procedures





Automatic ground balancing process

Helpful hardware projects (2007 – 2015)

Development, production, testing: Hardware implementation



Multifunctional wired/wireless serial cable – USB/Bluetooth \leftrightarrow Serial (TTL/RS232) adapter based on BTM-182 and CP2102 (2015)




MultiFDS: FTDI FT2232 based TTL Serial/RS232/JTAG adapter (2007)

Electronics Line 3000: Internet enabled security system (2003 – 2008)

Introduced: SOA and Long term high load functional testing methodology



Snapshot of real test case



Master Project Presentation

Internet accessible embedded system for distance measuring

Author:

Dilyana Panayotova

Technical University - Sofia, branch Plovdiv,
Department Electronics and Automation







Supervisor:

M.Sc. Dr. Valentin Mollov
Head of CE Department

Consultant:


Christo Radev
CS/IT Expert

Referee:




Measurement System

General idea description




Internet Controller

i386/eCOS Application – Modules Schematic



Internet Controller

eCOS Configuration – i386 PC Target



Internet Controller

eCOS Application – Main and Daemon modules




Measurement Controller

Hardware schematic design




Measurement Controller

Calculation mechanics



TU Plovdiv, BU Istanbul, Sony: Autonomous soccer playing AIBO robots (2000 – 2001)
RoboCup 2001 (Sony Four-Legged Robots League) participation: Balkan (Cerberus) international team



TU Plovdiv, BU Istanbul, Sony: Autonomous soccer playing AIBO robots (2000 – 2001)

Bulgarian team share: Acoustic communications, Behaviour, Locomotion, Multi-agent behaviour and System control

CERBERUS 2001 TEAM REPORT



Sophia University, Turkey
Technical University of Sofia, Bulgaria

R. Leman Alkan^{1*}
Ervin Bozaci²
Tuncay Cakici²
Cemal Dilek²
Cagdas Gencoglu²
Yilmaz Guneser²
Mustafa Kara²
Hakan Kara²
Huseyin Kara²
Alihan Kara²
Mehmet Kara²
Omer Kara²
Gurcan Yalcin²

¹Department of Computer Engineering, Bosphorus University, 34387, Beşiktaş, Istanbul, Turkey
²Department of Electrical and Electronics Engineering, Bosphorus University, 34387, Beşiktaş, Istanbul, Turkey

September 20, 2001

*Corresponding Author

TABLE OF CONTENTS

ACKNOWLEDGEMENTS	ii
I. INTRODUCTION	1
II. THE DEVELOPMENT TEAM	1
II.1 Turkish Team	1
II.2 Bulgarian Team	3
III. THE ALGORITHMS	4
III.1 System Architecture	4
III.2 The Architect	5
III.3 Vision	6
III.3.1 Color Recognition System	6
III.3.2 Object Recognition System	7
III.4 Localization	8
III.4.1 To Make a Color Table	8
III.4.2 Changes during the competition	16
III.4.3 Calculation of the Heading	16
III.4.4 Localization and Behaviors	17
III.4.5 Locomotion and Command Module	17
III.4.6 Vision	17
III.4.7 Behaviors	18
III.5 Planner	18
III.5.1 Planner for the Attacker	18
III.5.2 Commander module for player Behaviors	19
IV. ENVIRONMENT-DEVELOPMENT	21
IV.1 The Field and Lighting Conditions	21
IV.2 Software and Hardware	32
V. DEVELOPMENT PERIOD	33
VI. CHALLENGES	34
VI.1 Vision	34
VI.2 Challenges	34
VI.3 Challenge 1	34
VII. DISCUSSION AND CONCLUSIONS	37
VIII. RESOURCES	37
REFERENCES	38

The Cerberus team is a joint effort of Bosphorus University (Turkey) and Technical University of Sofia, Plovdiv branch (Bulgaria). The lead of the Cerberus project is Prof. Okuyan Kara, faculty member at the Electrical and Electronics Department of Bosphorus University and the UNESCO chair on Microelectronics.

I.1.1 Turkcell Team
The Cerberus team is a joint effort of Bosphorus University (Turkey) and Technical University of Sofia, Plovdiv branch (Bulgaria). The lead of the Cerberus project is Prof. Okuyan Kara, faculty member at the Electrical and Electronics Department of Bosphorus University and the UNESCO chair on Microelectronics.

II.1.1 Raytracing Analysis
The Cerberus team is a joint effort of Bosphorus University (Turkey) and Technical University of Sofia, Plovdiv branch (Bulgaria). The lead of the Cerberus project is Prof. Okuyan Kara, faculty member at the Electrical and Electronics Department of Bosphorus University and the UNESCO chair on Microelectronics.

II.1.2 The Architect
The Cerberus team is a joint effort of Bosphorus University (Turkey) and Technical University of Sofia, Plovdiv branch (Bulgaria). The lead of the Cerberus project is Prof. Okuyan Kara, faculty member at the Electrical and Electronics Department of Bosphorus University and the UNESCO chair on Microelectronics.

II.1.3 Vision
The Cerberus team is a joint effort of Bosphorus University (Turkey) and Technical University of Sofia, Plovdiv branch (Bulgaria). The lead of the Cerberus project is Prof. Okuyan Kara, faculty member at the Electrical and Electronics Department of Bosphorus University and the UNESCO chair on Microelectronics.

II.1.4 Localization
The Cerberus team is a joint effort of Bosphorus University (Turkey) and Technical University of Sofia, Plovdiv branch (Bulgaria). The lead of the Cerberus project is Prof. Okuyan Kara, faculty member at the Electrical and Electronics Department of Bosphorus University and the UNESCO chair on Microelectronics.

II.1.5 Behaviors
The Cerberus team is a joint effort of Bosphorus University (Turkey) and Technical University of Sofia, Plovdiv branch (Bulgaria). The lead of the Cerberus project is Prof. Okuyan Kara, faculty member at the Electrical and Electronics Department of Bosphorus University and the UNESCO chair on Microelectronics.

II.1.6 Planner
The Cerberus team is a joint effort of Bosphorus University (Turkey) and Technical University of Sofia, Plovdiv branch (Bulgaria). The lead of the Cerberus project is Prof. Okuyan Kara, faculty member at the Electrical and Electronics Department of Bosphorus University and the UNESCO chair on Microelectronics.

II.1.7 Commander module for player Behaviors
The Cerberus team is a joint effort of Bosphorus University (Turkey) and Technical University of Sofia, Plovdiv branch (Bulgaria). The lead of the Cerberus project is Prof. Okuyan Kara, faculty member at the Electrical and Electronics Department of Bosphorus University and the UNESCO chair on Microelectronics.

IV.1 ENVIRONMENT-DEVELOPMENT
The Cerberus team is a joint effort of Bosphorus University (Turkey) and Technical University of Sofia, Plovdiv branch (Bulgaria). The lead of the Cerberus project is Prof. Okuyan Kara, faculty member at the Electrical and Electronics Department of Bosphorus University and the UNESCO chair on Microelectronics.

IV.1.1 The Field and Lighting Conditions
The Cerberus team is a joint effort of Bosphorus University (Turkey) and Technical University of Sofia, Plovdiv branch (Bulgaria). The lead of the Cerberus project is Prof. Okuyan Kara, faculty member at the Electrical and Electronics Department of Bosphorus University and the UNESCO chair on Microelectronics.

IV.1.2 Software and Hardware
The Cerberus team is a joint effort of Bosphorus University (Turkey) and Technical University of Sofia, Plovdiv branch (Bulgaria). The lead of the Cerberus project is Prof. Okuyan Kara, faculty member at the Electrical and Electronics Department of Bosphorus University and the UNESCO chair on Microelectronics.

V.1 CHALLENGES
The Cerberus team is a joint effort of Bosphorus University (Turkey) and Technical University of Sofia, Plovdiv branch (Bulgaria). The lead of the Cerberus project is Prof. Okuyan Kara, faculty member at the Electrical and Electronics Department of Bosphorus University and the UNESCO chair on Microelectronics.

V.1.1 Vision
The Cerberus team is a joint effort of Bosphorus University (Turkey) and Technical University of Sofia, Plovdiv branch (Bulgaria). The lead of the Cerberus project is Prof. Okuyan Kara, faculty member at the Electrical and Electronics Department of Bosphorus University and the UNESCO chair on Microelectronics.

V.1.2 Challenges
The Cerberus team is a joint effort of Bosphorus University (Turkey) and Technical University of Sofia, Plovdiv branch (Bulgaria). The lead of the Cerberus project is Prof. Okuyan Kara, faculty member at the Electrical and Electronics Department of Bosphorus University and the UNESCO chair on Microelectronics.

V.1.3 Challenge 1
The Cerberus team is a joint effort of Bosphorus University (Turkey) and Technical University of Sofia, Plovdiv branch (Bulgaria). The lead of the Cerberus project is Prof. Okuyan Kara, faculty member at the Electrical and Electronics Department of Bosphorus University and the UNESCO chair on Microelectronics.

VII.1 DISCUSSION AND CONCLUSIONS
The Cerberus team is a joint effort of Bosphorus University (Turkey) and Technical University of Sofia, Plovdiv branch (Bulgaria). The lead of the Cerberus project is Prof. Okuyan Kara, faculty member at the Electrical and Electronics Department of Bosphorus University and the UNESCO chair on Microelectronics.

VII.2 RESOURCES
The Cerberus team is a joint effort of Bosphorus University (Turkey) and Technical University of Sofia, Plovdiv branch (Bulgaria). The lead of the Cerberus project is Prof. Okuyan Kara, faculty member at the Electrical and Electronics Department of Bosphorus University and the UNESCO chair on Microelectronics.

REFERENCES

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

68

69

70

71

72

73

74

75

76

77

78

79

80

81

82

83

84

85

86

87

88

89

90

91

92

93

94

95

96

97

98

99

100

101

102

103

104

105

106

107

108

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

148

149

150

151

152

153

154

155

156

157

158

159

160

161

162

163

164

165

166

167

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

217

218

Multimedia, paper, web and presentations design projects (1998 – 2019)



Multimedia Presentation

Audio and Multimedia CD's

In 1998 came to life an idea of creating a Multimedia Presentation and Audio Data preserving achieved singing level and development trends of one young opera singer.

These products were created thanks to the volunteer work of experts skilled in their own fields:

- Lili Banevatcheva - pianist
- Ivan Banevatchev - recording
- Christo Radov - multimedia designer.

Everyone, who made place at the creation of these new media, hopes that greater will be the pleasure of watching the products they have given you a new way to dive into the knowledge that they have captured through the times.

System Requirements

To successfully run this Multimedia Presentation, you need a computer that meets the following minimum of requirements:

- Pentium 173 (or higher), 32 MB recommended
- 16 MB RAM, 32 MB recommended
- 1.3 GB free disk space
- 2X or faster CD-RW/DVD ROM recommended
- SVGA colour monitor, display card, 800 x 600, 16-bit colour mode
- Win 98/ME/2000/XP, Mac OS X, Linux
- Win-based compatible sound device and a graphics software installed and tested under Windows
- Modem or network adapter (10Base-T) recommended
- Ethernet card, 10/100 Mbit/s recommended
- WinMedia 7, MP3, 4 or later recording system
- MTC (Multimedia Technical Corporation) recording software (CD-RW/DVD ROM 2.2X or faster recommended) is included in the CD-ROM
- External microphone, 1/8" jack, 3.5 mm, 16 bit, 44.1 kHz audio system. For more information use the "Read Me" file on the Multimedia Presentation CD.

This is not a list of what is required to run this Multimedia Presentation. After inserting of CD into one of CD-ROM drives, the system will automatically start the presentation. You can easily create your own "Read Me" file for this Multimedia Presentation.



Ivan Kabamitov - Baritone

Multimedia Presentation

- Audio CD - 12 songs (62:36)
- Multimedia Presentation CD
- 14 Audio clips (1:14)
- 14 Video clips (54:36)
- 12 Texts & 12 Pictures

Product Information
This is not a list of what is required to run this Multimedia Presentation. After inserting of CD into one of CD-ROM drives, the system will automatically start the presentation. You can easily create your own "Read Me" file for this Multimedia Presentation.

Ivan Kabamitov - Baritone

Multimedia Presentation

Multimedia CD - Audio

F. Offenbach song - "Mignonleise" 2:18

2. Faustino Aragón - "Star duale studio press" 2:09

3. Todor Popov - "Produljivo" 3:04

4. Tsvetan Tsvetkov - "Diva diva" 2:00

5. Tsvetan Tsvetkov - "Eugene Onegin" aria of Despina, Act 2 3:01

6. Tsvetan Tsvetkov - "Eugene Onegin" aria of Despina, Act 2 2:47

7. Tsvetan Tsvetkov - "Faust" aria of Marguerite, Act 2 3:01

8. Tsvetan Tsvetkov - "Faust" aria of Marguerite, Act 2 2:48

9. Tsvetan Tsvetkov - "Carmen" 2:44

10. Tsvetan Tsvetkov - "Carmen" 2:44

11. Tsvetan Tsvetkov - "Carmen" 2:44

12. Tsvetan Tsvetkov - "Carmen" 2:44

13. Tsvetan Tsvetkov - "Carmen" 2:44

14. Tsvetan Tsvetkov - "Carmen" 2:44

F. Offenbach song - "Mignonleise" 2:23

2. Faustino Aragón - "Star duale studio press" 2:53

3. Todor Popov - "Produljivo" 3:49

4. Todor Popov - "Produljivo" 3:49

5. Tsvetan Tsvetkov - "Diva diva" 2:00

6. Tsvetan Tsvetkov - "Eugene Onegin" aria of Despina, Act 2 3:01

7. Tsvetan Tsvetkov - "Faust" aria of Marguerite, Act 2 3:01

8. Tsvetan Tsvetkov - "Faust" aria of Marguerite, Act 2 2:48

9. Tsvetan Tsvetkov - "Carmen" 2:44

10. Tsvetan Tsvetkov - "Carmen" 2:44

11. Tsvetan Tsvetkov - "Carmen" 2:44

12. Tsvetan Tsvetkov - "Carmen" 2:44

13. Tsvetan Tsvetkov - "Carmen" 2:44

14. Tsvetan Tsvetkov - "Carmen" 2:44

F. Offenbach song - "Mignonleise" 2:23

2. Faustino Aragón - "Star duale studio press" 2:53

3. Todor Popov - "Produljivo" 3:49

4. Todor Popov - "Produljivo" 3:49

5. Tsvetan Tsvetkov - "Diva diva" 2:00

6. Tsvetan Tsvetkov - "Eugene Onegin" aria of Despina, Act 2 3:01

7. Tsvetan Tsvetkov - "Faust" aria of Marguerite, Act 2 3:01

8. Tsvetan Tsvetkov - "Faust" aria of Marguerite, Act 2 2:48

9. Tsvetan Tsvetkov - "Carmen" 2:44

10. Tsvetan Tsvetkov - "Carmen" 2:44

11. Tsvetan Tsvetkov - "Carmen" 2:44

12. Tsvetan Tsvetkov - "Carmen" 2:44

13. Tsvetan Tsvetkov - "Carmen" 2:44

14. Tsvetan Tsvetkov - "Carmen" 2:44

F. Offenbach song - "Mignonleise" 2:23

2. Faustino Aragón - "Star duale studio press" 2:53

3. Todor Popov - "Produljivo" 3:49

4. Todor Popov - "Produljivo" 3:49

5. Tsvetan Tsvetkov - "Diva diva" 2:00

6. Tsvetan Tsvetkov - "Eugene Onegin" aria of Despina, Act 2 3:01

7. Tsvetan Tsvetkov - "Faust" aria of Marguerite, Act 2 3:01

8. Tsvetan Tsvetkov - "Faust" aria of Marguerite, Act 2 2:48

9. Tsvetan Tsvetkov - "Carmen" 2:44

10. Tsvetan Tsvetkov - "Carmen" 2:44

11. Tsvetan Tsvetkov - "Carmen" 2:44

12. Tsvetan Tsvetkov - "Carmen" 2:44

13. Tsvetan Tsvetkov - "Carmen" 2:44

14. Tsvetan Tsvetkov - "Carmen" 2:44

F. Offenbach song - "Mignonleise" 2:23

2. Faustino Aragón - "Star duale studio press" 2:53

3. Todor Popov - "Produljivo" 3:49

4. Todor Popov - "Produljivo" 3:49

5. Tsvetan Tsvetkov - "Diva diva" 2:00

6. Tsvetan Tsvetkov - "Eugene Onegin" aria of Despina, Act 2 3:01

7. Tsvetan Tsvetkov - "Faust" aria of Marguerite, Act 2 3:01

8. Tsvetan Tsvetkov - "Faust" aria of Marguerite, Act 2 2:48

9. Tsvetan Tsvetkov - "Carmen" 2:44

10. Tsvetan Tsvetkov - "Carmen" 2:44

11. Tsvetan Tsvetkov - "Carmen" 2:44

12. Tsvetan Tsvetkov - "Carmen" 2:44

13. Tsvetan Tsvetkov - "Carmen" 2:44

14. Tsvetan Tsvetkov - "Carmen" 2:44

F. Offenbach song - "Mignonleise" 2:23

2. Faustino Aragón - "Star duale studio press" 2:53

3. Todor Popov - "Produljivo" 3:49

4. Todor Popov - "Produljivo" 3:49

5. Tsvetan Tsvetkov - "Diva diva" 2:00

6. Tsvetan Tsvetkov - "Eugene Onegin" aria of Despina, Act 2 3:01

7. Tsvetan Tsvetkov - "Faust" aria of Marguerite, Act 2 3:01

8. Tsvetan Tsvetkov - "Faust" aria of Marguerite, Act 2 2:48

9. Tsvetan Tsvetkov - "Carmen" 2:44

10. Tsvetan Tsvetkov - "Carmen" 2:44

11. Tsvetan Tsvetkov - "Carmen" 2:44

12. Tsvetan Tsvetkov - "Carmen" 2:44

13. Tsvetan Tsvetkov - "Carmen" 2:44

14. Tsvetan Tsvetkov - "Carmen" 2:44

F. Offenbach song - "Mignonleise" 2:23

2. Faustino Aragón - "Star duale studio press" 2:53

3. Todor Popov - "Produljivo" 3:49

4. Todor Popov - "Produljivo" 3:49

5. Tsvetan Tsvetkov - "Diva diva" 2:00

6. Tsvetan Tsvetkov - "Eugene Onegin" aria of Despina, Act 2 3:01

7. Tsvetan Tsvetkov - "Faust" aria of Marguerite, Act 2 3:01

8. Tsvetan Tsvetkov - "Faust" aria of Marguerite, Act 2 2:48

9. Tsvetan Tsvetkov - "Carmen" 2:44

10. Tsvetan Tsvetkov - "Carmen" 2:44

11. Tsvetan Tsvetkov - "Carmen" 2:44

12. Tsvetan Tsvetkov - "Carmen" 2:44

13. Tsvetan Tsvetkov - "Carmen" 2:44

14. Tsvetan Tsvetkov - "Carmen" 2:44

F. Offenbach song - "Mignonleise" 2:23

2. Faustino Aragón - "Star duale studio press" 2:53

3. Todor Popov - "Produljivo" 3:49

4. Todor Popov - "Produljivo" 3:49

5. Tsvetan Tsvetkov - "Diva diva" 2:00

6. Tsvetan Tsvetkov - "Eugene Onegin" aria of Despina, Act 2 3:01

7. Tsvetan Tsvetkov - "Faust" aria of Marguerite, Act 2 3:01

8. Tsvetan Tsvetkov - "Faust" aria of Marguerite, Act 2 2:48

9. Tsvetan Tsvetkov - "Carmen" 2:44

10. Tsvetan Tsvetkov - "Carmen" 2:44

11. Tsvetan Tsvetkov - "Carmen" 2:44

12. Tsvetan Tsvetkov - "Carmen" 2:44

13. Tsvetan Tsvetkov - "Carmen" 2:44

14. Tsvetan Tsvetkov - "Carmen" 2:44

F. Offenbach song - "Mignonleise" 2:23

2. Faustino Aragón - "Star duale studio press" 2:53

3. Todor Popov - "Produljivo" 3:49

4. Todor Popov - "Produljivo" 3:49

5. Tsvetan Tsvetkov - "Diva diva" 2:00

6. Tsvetan Tsvetkov - "Eugene Onegin" aria of Despina, Act 2 3:01

7. Tsvetan Tsvetkov - "Faust" aria of Marguerite, Act 2 3:01

8. Tsvetan Tsvetkov - "Faust" aria of Marguerite, Act 2 2:48

9. Tsvetan Tsvetkov - "Carmen" 2:44

10. Tsvetan Tsvetkov - "Carmen" 2:44

11. Tsvetan Tsvetkov - "Carmen" 2:44

12. Tsvetan Tsvetkov - "Carmen" 2:44

13. Tsvetan Tsvetkov - "Carmen" 2:44

14. Tsvetan Tsvetkov - "Carmen" 2:44

F. Offenbach song - "Mignonleise" 2:23

2. Faustino Aragón - "Star duale studio press" 2:53

3. Todor Popov - "Produljivo" 3:49

4. Todor Popov - "Produljivo" 3:49

5. Tsvetan Tsvetkov - "Diva diva" 2:00

6. Tsvetan Tsvetkov - "Eugene Onegin" aria of Despina, Act 2 3:01

7. Tsvetan Tsvetkov - "Faust" aria of Marguerite, Act 2 3:01

8. Tsvetan Tsvetkov - "Faust" aria of Marguerite, Act 2 2:48

9. Tsvetan Tsvetkov - "Carmen" 2:44

10. Tsvetan Tsvetkov - "Carmen" 2:44

11. Tsvetan Tsvetkov - "Carmen" 2:44

12. Tsvetan Tsvetkov - "Carmen" 2:44

13. Tsvetan Tsvetkov - "Carmen" 2:44

14. Tsvetan Tsvetkov - "Carmen" 2:44

F. Offenbach song - "Mignonleise" 2:23


2. Faustino Aragón - "Star duale studio press" 2:53

3. Todor Popov - "Produljivo" 3:49


4. Todor Popov - "Produljivo" 3:49

5. Tsvetan Tsvetkov - "Diva diva" 2:00


Student's projects and graduation works guidance (1998 – 2003)




Finite-state machine: Ocuntorite



Object Oriented Programming: Game Kalah (Mancala)



Iterative solving of linear systems



Information & Delivery System






Image processing – threshold



Laser diode projector (micro controller programming, project builder and programmer)




Master of Engineering in Embedded Systems Design, ALaRI, Lugano, Switzerland



Web Services Evaluation Apache Axis vs. Mind Electric Glue

Anastasiya Radeva

ATLAS Online Software Meeting, 9/9/2003



Summer Student Program 2003, ATLAS, CERN, Geneva, Switzerland

9/9/2003 Web Services Evaluation, Axis vs. Glue 6

Doctoral dissertation: mathematical support, paper and presentation design and work out (1998 – 2000)

Subject: Green Bean Germplasm in an EX SITU Collection – Evaluation, Identification, Conservation and Use


Time Page	Sources
Abstract	Coultures
Content	Publications
Chapter	123456789
Please, send Your Comment	

Resistance to bean weevil (*Ac. obtectus* Say)

For the 17-year tested period, a total of 2873 accessions, of which 1376 local, and 1497 introduced forms, were analyzed. A total of 708 gene sources were selected for both groups, of which 396 from local and 312 from introduced accessions.


Distribution by years of study

During all years of study, in addition to the group of 100% resistant accessions, a group of slightly resistant ones was also created. There were selected 299 accessions, the resistance of which was over 90%. The percentage ratio between the resistant and slightly damaged accessions in both groups is given in the figure.




Computer work and design (GIS)


Geographic distribution of the collection



Among the European countries, the highest number of resistant accessions were supplied from Germany, Hungary and France. Of the non-European (figure above) countries, the largest group originated from Columbia – 154 accessions, followed by Brazil – 10, Mexico – 8, USA – 8, China and Korea – by 5, and Canada – 4.




Professional web site



Mathematical results, printed and presentation materials

G.L.T. Ltd., Plovdiv: System for Roentgen-Fluorescence Analysis of heavy metals concentration (1996 – 1997)
 Development, programing, testing, introduction: Embedded and desktop software implementation



RFA work station and computer suit



Program for optimization of RFA equations

Non-ferrous metal mill JSC - Plovdiv

X-ray Fluorescence Laboratory
 24/2/97 - 12:23:37

Lead production
 Material: Lead concentrate
 System recalibration started on: 7/2/97

Coefficients of the equation for: Zn

Coefficient * Parameter
Zn % = -2.227568
+0.284827 * Zn
-0.000791 * Zn*Bg


Correlation coefficient R = 0.9721
 Dispersion S = 0.3248

Changed intensities of control standards

#	Sample Chem. analysis	R F A	Diversion
1	413	6.930	-0.193
2	474	7.980	+0.211
3	477	8.900	-0.218
4	487	7.450	+0.081
5	614	9.330	-0.293
6	439	6.250	+0.519
7	533	6.330	-0.358
8	421	6.500	+0.094
9	467	8.420	+0.464
10	472	8.290	-0.115
11	488	8.690	-0.288
12	519	7.680	+0.096

Operator: / / /

Protocol for system recalibration





Pallet ID = 14




Pallet ID = 16




Destination = 0EA7




ERP system for low temperature warehouses based on barcodes, Progress Application Server (Windows 2003 / 7) and mobile application for Psion Teklogix 7530 G2 device (Windows CE 5.0 & .NET CF 2.0)



Multi-office Intranet system for selling in real-time




Plant automation system based on weighing and QNX



Automation of accounting system Logos

Nova Ltd., Plovdiv: Powerful computing system based on Inmos Transputers (1989 – 1994)
Development, production, testing, programing and application: PC board, Windows server, Lynx-T language, IAEA calculations




```



subnet /Cluster {
    Reset { driver; ~00; tram_ra.d}

    processor 00 { ~IO,      , ~01, ~02; }
    processor 01 { ~00,      , ~03; run -e /helios/lib/fs fs scsi; }
    processor 02 {      , ~00, ~03, ~04; run /helios/lib/lock; }
    processor 03 { ~02, ~01,      , ~05; }
    processor 04 {      , ~02, ~05, ~06; }
    processor 05 { ~04, ~03,      , ~07; }
    processor 06 {      , ~04, ~07,      ; }
    processor 07 { ~06, ~05,      ,      ; }
    processor IO { ~00; IO }
}


```





PC board hosting up to 10 transputers and programmable link switch



Language, tools and system for massive parallel computing




Bulgarian Academy of Science, Central Laboratory on Automation and Scientific Instrumentation, Plovdiv (1983 – 1988)
Development, production, testing and programing: VME-bus Instrumentation System based on MC68000 (Interlab)




Bulgarian Academy of Science, Central Laboratory on Automation and Scientific Instrumentation, Plovdiv (1983 – 1988)

Development, production, testing and programing: CAMAC Instrumentation Systems



Basic system in CAMAC standard based on MC6800 – CLASI 270



Basic system in CAMAC standard based on LSI-1123 – CLASI 290




IEEE 488 for MC6800 based CAMAC module




MC6800 based floppy disk subsystem for LSI-1123



MC6800/MC6840 based music CAMAC module



Terminal card for Apple II



Bulgarian singing Apple II



Punch tape subsystem for LSI-1123 I/O




Bulgarian Academy of Science, Laboratory of Applied Physics, Quantum Electronics Department, Plovdiv (1979 – 1983)
 Design, implementation, investigation, application: Powerful pulse-periodic TEA CO₂ Laser



Industrial TEA CO₂ Laser 1300-M

TECHNICAL PARAMETERS:

Wavelength	- 10.6 microns,
Pulse power (maximum)	- 100 MW,
Impulse energy (maximum)	- 6 J,
Pulse repetition rate	- 0.1 - 50 Hz,
Average power (maximum)	- 50 W,
Pulse duration	- 0.06 - 2 μ s,
Gas consumption (CO ₂ : N ₂ : He = 1: 1: 8)	- 1 l / min,
Water consumption	- 10 l / min,
Power supply 3 x 380 V / 50 Hz	- 2.5 kW,
Laser head size	- 1100/880/510 mm,
Power supply unit size	- 1600/900/700 mm,



Remarkable achievements at development process



Industrial TEA CO₂ Laser

XI National Exhibition

Golden medals from Technical and Scientific Creation of Youth




Laser marking system


XII National Exhibition

Golden medals from Technical and Scientific Creation of Youth


Bulgarian Academy of Science, Laboratory of Applied Physics, Quantum Electronics Department, Plovdiv (1979 – 1983)
Design, implementation, programing and application: MC6800 based control system for laser applications




Prototypes of MC6800 based control system and powerful TEA CO₂ Laser



Thin films trimming




CO₂/N₂ laser tuning, scribing, engraving etc.



Glass marking






Metal engraving









TEA CO₂ laser deposition

Sofia University, Faculty of Physics, Quantum Electronics Department (1977 – 1979)
 Graduation work thesis: X-ray emission from laser plasma in a strong electric field




Experiment schematics and implementation




Two-dimensional photo effect in surface semiconductor transition and large area devices based thereon


Production process of position sensitive device based on two-dimensional photo effect in surface semiconductor transition




Ion Implantation of Si p-substrate





The result is thin Si disk with n-p transition on its surface





High vacuum system



Vacuum chamber used to put thin Al layer by evaporation



Theory and proof of concept by measurement




**Co-founder of astronomy and optics clubs; active member of amateur radio and electronics clubs
High technical school of mechanics, Plovdiv (1968 – 1972); Voluntary organization for defence assistance (1967 – 1972);
District station of the young technicians (1968 – 1972); Sofia University, Faculty of Physics, Faculty Observatory (1974 – 1977)**



Optical club at the faculty observatory




Electronic device for image processing at the faculty observatory



Construction of amateur observatory



 **Telescope reflector with 10 cm mirror: participation in IV National Exhibition for Technical and Scientific Creation of Youth, 1971, Golden medal**



 **Telescope reflector with 32 cm mirror: participation in V National Exhibition for Technical and Scientific Creation of Youth, 1973, Golden medal**

Scholar essay: Development of the philosophical categories for space and time in mathematics and physics, 1972
Participation in Mathematical school for Olympic Competitors (1968 – 1972) and IV National Conference on Physics, Sofia, 1973

TRAMONTA

ЦЕНТРАЛНА СТАНЦИЯ НА МЛАДИТЕ ТЕХНИЦИ

НАГРАЖДАВА

Христо Радев
Джитехническа гимназия

гр. (2) **Ловдив**, окръг
за активно участие в **шестия** ПРЕГЛЕД
НА ТЕХНИЧЕСКОТО И НАУЧНО ТВОРЧЕСТВО НА
МЛАДЕНЦА И ДЕЦАТА – **Четвърта реноди-
анска конференция по физика**

София, 13 IV 1973 година

ДИРЕКТОР:



• 88 •

1. $\sum_{k=1}^{\infty} \frac{1}{k^2}$ is convergent by comparison test.
 $\left(\frac{1}{k^2} < \frac{1}{k!}\right)$
 since $\sum_{k=1}^{\infty} \frac{1}{k!}$ is the sum of the terms in $\sum_{k=0}^{\infty} \frac{1}{k!} = e^1 = e$
 so, $\sum_{k=1}^{\infty} \frac{1}{k!}$ is also convergent by limit comparison test
 $\Rightarrow \sum_{k=1}^{\infty} \frac{1}{k^2}$ is also convergent.

S. fuscus S. *blattae* 33
 INFLUENCE OF VARIOUS CONCENTRATIONS OF H_2O_2 ON HYDROLYSIS
 OF C_6H_{12} BY $\text{C}_6\text{H}_5\text{COOH}$ AND $\text{C}_6\text{H}_5\text{COCl}$
 IN THE PRESENCE OF Fe^{2+}
 $\text{C}_6\text{H}_{12} \text{--} \text{C}_6\text{H}_5\text{COOH} \text{--} \text{C}_6\text{H}_5\text{COCl} \text{--} \text{H}_2\text{O}_2$
 Fe^{2+}
 $\text{C}_6\text{H}_{12} \text{--} \text{C}_6\text{H}_5\text{COOH} \text{--} \text{C}_6\text{H}_5\text{COCl} \text{--} \text{H}_2\text{O}_2$
 Fe^{2+}
 Peroxidase catalyzes the decomposition of H_2O_2 . It decomposes H_2O_2 in the presence of Fe^{2+} and $\text{C}_6\text{H}_5\text{COOH}$ or $\text{C}_6\text{H}_5\text{COCl}$ to form H_2O and O_2 . The reaction is as follows:
 $\text{H}_2\text{O}_2 + \text{Fe}^{2+} \rightarrow \text{H}_2\text{O} + \text{O}_2 + \text{Fe}^{3+}$
 $\text{H}_2\text{O}_2 + \text{Fe}^{3+} + \text{C}_6\text{H}_5\text{COOH} \rightarrow \text{H}_2\text{O} + \text{O}_2 + \text{Fe}^{2+} + \text{C}_6\text{H}_5\text{COCl}$
 In the presence of $\text{C}_6\text{H}_5\text{COOH}$ or $\text{C}_6\text{H}_5\text{COCl}$, the hydrolysis of C_6H_{12} is increased.
 3. Influence of H_2O_2 concentration
 It is known that the influence of H_2O_2 concentration on the hydrolysis of C_6H_{12} by $\text{C}_6\text{H}_5\text{COOH}$ or $\text{C}_6\text{H}_5\text{COCl}$ is as follows:
 H_2O_2 concentration is proportional to the hydrolysis rate for small values of H_2O_2 concentration, but for large values of H_2O_2 concentration, the hydrolysis rate decreases. This is due to the fact that the peroxidase is inhibited at high concentrations of H_2O_2 .

Задача 10. Решите систему линейных уравнений методом Гаусса:

$$\begin{cases} x_1 + 2x_2 - x_3 = 1 \\ 2x_1 + 3x_2 + x_3 = 0 \\ x_1 - x_2 + 4x_3 = 3 \end{cases}$$

Матрица коэффициентов и вектор-столбец приращений:

$$A = \begin{pmatrix} 1 & 2 & -1 \\ 2 & 3 & 1 \\ 1 & -1 & 4 \end{pmatrix}, \quad b = \begin{pmatrix} 1 \\ 0 \\ 3 \end{pmatrix}$$

Матрица коэффициентов в исходной системе:

$$B_{123} = \begin{pmatrix} 1 & 2 & -1 \\ 2 & 3 & 1 \\ 1 & -1 & 4 \end{pmatrix}$$

Матрица коэффициентов в системе с единичным коэффициентом при x_1 :

$$B_{123}^{(1)} = \begin{pmatrix} 1 & 2 & -1 \\ 2 & 3 & 1 \\ 1 & -1 & 4 \end{pmatrix}$$

Матрица коэффициентов в системе с единичным коэффициентом при x_2 :

$$B_{123}^{(2)} = \begin{pmatrix} 1 & 2 & -1 \\ 0 & 1 & 3 \\ 1 & -1 & 4 \end{pmatrix}$$

Матрица коэффициентов в системе с единичным коэффициентом при x_3 :

$$B_{123}^{(3)} = \begin{pmatrix} 1 & 2 & -1 \\ 0 & 1 & 3 \\ 0 & 1 & 5 \end{pmatrix}$$

Матрица коэффициентов в системе с единичным коэффициентом при x_2 :

$$B_{123}^{(4)} = \begin{pmatrix} 1 & 2 & -1 \\ 0 & 1 & 3 \\ 0 & 0 & 2 \end{pmatrix}$$

Матрица коэффициентов в системе с единичным коэффициентом при x_3 :

$$B_{123}^{(5)} = \begin{pmatrix} 1 & 2 & -1 \\ 0 & 1 & 3 \\ 0 & 0 & 1 \end{pmatrix}$$

Матрица коэффициентов в исходной системе:

$$B_{123} = \begin{pmatrix} 1 & 2 & -1 \\ 2 & 3 & 1 \\ 1 & -1 & 4 \end{pmatrix}$$

Матрица коэффициентов в системе с единичным коэффициентом при x_1 :

$$B_{123}^{(6)} = \begin{pmatrix} 1 & 2 & -1 \\ 2 & 3 & 1 \\ 1 & -1 & 4 \end{pmatrix}$$

Матрица коэффициентов в системе с единичным коэффициентом при x_2 :

$$B_{123}^{(7)} = \begin{pmatrix} 1 & 2 & -1 \\ 0 & 1 & 3 \\ 1 & -1 & 4 \end{pmatrix}$$

Матрица коэффициентов в системе с единичным коэффициентом при x_3 :

$$B_{123}^{(8)} = \begin{pmatrix} 1 & 2 & -1 \\ 0 & 1 & 3 \\ 0 & 1 & 5 \end{pmatrix}$$

Матрица коэффициентов в системе с единичным коэффициентом при x_2 :

$$B_{123}^{(9)} = \begin{pmatrix} 1 & 2 & -1 \\ 0 & 1 & 3 \\ 0 & 0 & 2 \end{pmatrix}$$

Матрица коэффициентов в системе с единичным коэффициентом при x_3 :

$$B_{123}^{(10)} = \begin{pmatrix} 1 & 2 & -1 \\ 0 & 1 & 3 \\ 0 & 0 & 1 \end{pmatrix}$$

Програма на IV Републиканска конференция по физика Program of the IV Republican Conference in Physics

— 6 —
внешними видами этого архитектурного вида
или изображениями, воспроизведенными в архитек-
турном и декоративном искусстве, настенных, скуль-
птурных


В итоге не употреблено выражение «если», а применено не к первому или к последнему, а к обоим. Но смысл этого не изменяется, так как оно выражает аналогичную мысль. Такое выражение можно считать не пропущенным, будучи сочтеным лишь повторением. Второго образца являются выражения вида

Канал У в промышленности Венгрии получил широкое распространение. Число каналов в промышленности Венгрии в 1950 г. составляло 1000 км, а в 1955 г. — 2000 км. Каналы в промышленности венгерской промышленности делятся на две категории: каналы для транспортировки нефти и нефтепродуктов и каналы для транспортировки химикатов.

* Не пригоден по износу.

Справедливые затраты капитальных износов на производство и прокат. Продолжительность производственных процессов, или这么说, в производстве, определяется как сумма производственного времени и производственного износа. Но не в производственных процессах, производственные износы не являются фактором, влияющим на стоимость единицы продукции.

High school of mechanics, Plovdiv: Internal combustion engines speciality, School karting club (1968 – 1972)
Graduation work thesis: Investigation of the combustion processes in diesel engines



Test suit for adjustment of fuel pumps and nozzles for diesel engines - repairing and testing as a part of graduation work

中国社会科学院研究生院

Литература.


и вспомогательные ткани. Поэтому мы предполагаем, что в основе гипертрофии лежит не только избыточное питание, но и нарушение функций эндокринной системы, в частности надпочечников. Г. О. Григорьев и Г. Г. Григорьева считают, что гипертрофия почек у детей может быть обусловлена нарушением функций щитовидной железы.

ISSN 1062-1024 • 2010 • 36(1)

	1	2	3
Баланс	0,000	0,000	-
Приход	0,075	0,065	0,006
Начисл.	0,000	0,007	0,000
Списан. из р/с	0,000	0,000	0,000

В. В. Струнин, директор Государственного музея истории религии в Москве, считает, что введение в музейных экспозициях изображений иконы Божией Матери «Знамение» в честь праздника Казанской иконы Божией Матери в 1991 году было бы неуместным.

4 www.EasyEngineering.net



Co-founder and active member of the school karting club (in cooperation with the sport cars station Bulgaralpine of Bulgarreno plant): design, crafting, race training; participation in competitions and IV National Exhibition of Technical and Scientific Creation of Youth, 1971, Silver medal for "Racing karting".

4. Составление паспорта изображения	33
5. Виды и их описание	33
Бланк для выдачи паспорта	33
Кодировка на бланке	33
Составление бланка	33
Кодировка	33
Кодировка паспорта	33
Кодировка паспорта	33
Кодировка	33
Кодировка в бланке	33
Составление	33
Примечание	33

